

High levels of performance
throughout its life
and up to two years additional use

MICHELIN AGRIBIB

Traction



Service life



Robustness



High levels of performance throughout its life

- Optimal traction level
- Special tread pattern for excellent self-cleaning capacity


Service life

- Deep tread lugs for a longer service life

Robustness

- Proven radial casing endurance
- Damage-resistant rubber

Traction index



* Source: MICHELIN test and research center (Ladoux)
Calculation: average calculated on 13 popular sizes on the standard market

Source: Analytical test performed on the test tracks at the MICHELIN test and research centre (Ladoux)
Test conditions: clay/chalky soil – Tyre size: 18.4 R38



**From 60
to 170 HP***
(dependant on tyre size)

*** And up to 500 HP with twin wheels (42", 46", 50")**



Optimised tread pattern

- Lug angle 45° for better transfer of tractive force to the ground
- Hinge in the centre of the tread aids self-cleaning

Deep tread lugs

- R1W lug (lug depth as defined by the TRA standard)
- Lug design: straight profile

Damage-resistant rubber

Sizes

9.5	R24 TL 107A8/104B	380/85 R30 TL 135A8/135B	380/95 R38 TL 147A8/147B	NEW
11.2	R24 TL 114A8/111B	420/90 R30 TL 147A8/147B	420/85 R38 TL 144A8/144B	
12.4	R24 TL 119A8/116B	18.4 R34 TL 144A8/141B	520/85 R38 TL 155A8/155B	
13.6	R24 TL 121A8/118B	320/85 R34 TL 133A8/130B	480/80 R42 TL 156A8/156B	
14.9	R24 TL 126A8/123B	380/85 R34 TL 137A8/137B	520/85 R42 TL 157A8/157B	
16.9	R24 TL 134A8/131B	420/85 R34 TL 142A8/142B	420/80 R46 TL 151A8/148B	
12.4	R28 TL 121A8/118B	12.4 R36 TL 124A8/121B	480/80 R46 TL 158A8/158B	
13.6	R28 TL 123A8/120B	12.4 R38 TL 125A8/122B	520/85 R46 TL 158A8/155B	
14.9	R28 TL 128A8/125B	13.6 R38 TL 128A8/125B	480/80 R50 TL 159A8/159B	
16.9	R28 TL 136A8/133B	18.4 R38 TL 146A8/143B	480/95 R50 TL 164A8/164B	NEW
16.9	R30 TL 137A8/134B	20.8 R38 TL 153A8/150B		
18.4	R30 TL 142A8/139B	380/80 R38 TL 142A8/139D		



Characteristics of MICHELIN standard radial tyres MICHELIN AGRIBIB

Ø inches	Description	CAI	Tyre characteristics				Rim widths ⁽¹⁾ inches	Tube ⁽²⁾	75% internal volume liters	
			S mm	D mm	R' mm	R.C. mm				
24	9.5 R24 107A8/104B TL AGRIBIB	123932	247	1040	472	3097	W8 W7	686	64	
	11.2 R24 114A8/111B TL AGRIBIB	123864	294	1092	498	3292	W10 W9	692	92	
	12.4 R24 119A8/116B TL AGRIBIB	123788	324	1149	520	3420	W11 W10	692	115	
	13.6 R24 121A8/118B TL AGRIBIB	123868	366	1197	539	3559	W12 W11	700	151	
	14.9 R24 126A8/123B TL AGRIBIB	123848	408	1259	561	3733	W13 W12 W11	703	187	
	16.9 R24 134A8/131B TL AGRIBIB	123854	460	1330	586	3935	DW15L W14L DW14L W15L	710	243	
28	12.4 R28 121A8/118B TL AGRIBIB	123832	322	1262	577	3764	W11 W10	726	134	
	13.6 R28 123A8/120B TL AGRIBIB	123782	372	1308	592	3893	W12 W11	732	172	
	14.9 R28 128A8/125B TL AGRIBIB	123850	403	1358	612	4050	W13 W12	821	210	

(1) The reference rim is shown in bold type.
(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (January 2015). Technical data are subject to change without prior notice.



From 60 to 170 HP*

(dependant on tyre size)

* And up to 500 HP with twin wheels
(42", 46", 50")



Pressure (bar) and (psi) - Load per tyre in kg ⁽³⁾ - (4) - (5)																
	Bar Psi	0,40 ⁽⁶⁾ 6	0,50 ⁽⁷⁾ 7	0,60 9	0,80 12	1,00 15	1,20 17	1,40 20	1,60 23	1,80 26	1,90 28	2,00 29	2,20 32	2,40 35	2,60 38	2,80 41
10 km/h 30 km/h 40 km/h 50 km/h			750 580	860 680 630 590	950 750 700 650	1 045 825 770 715	1 135 895 840 775	1 230 970 910 840	1 320 1 040 980 900	1 415	1 460					
10 km/h 30 km/h 40 km/h 50 km/h			900 710	1 040 820 770 720	1 150 910 850 795	1 265 995 935 870	1 375 1 085 1 015 940	1 490 1 170 1 100 1 015	1 600 1 260 1 180 1 090	1 715	1 770					
10 km/h 30 km/h 40 km/h 50 km/h			1 040 810	1 200 950 880 830	1 330 1 050 975 915	1 460 1 155 1 070 1 000	1 590 1 255 1 170 1 080	1 715 1 360 1 265 1 165	1 845 1 460 1 360 1 250	1 975	2 040					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		555	690 1 110 870	825 1 280 1 010 940 870	915 1 420 1 120 1 040 960	1 005 1 555 1 225 1 145 1 050	1 095 1 695 1 335 1 245 1 140	1 185 1 835 1 440 1 350 1 230	1 275 1 970 1 550 1 450 1 320	2 110	2 180					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		660	820 1 300 1 020	975 1 500 1 180 1 110 1 020	1 080 1 660 1 310 1 230 1 125	1 185 1 825 1 435 1 345 1 230	1 285 1 985 1 565 1 465 1 340	1 390 2 145 1 690 1 580 1 445	1 495 2 310 1 820 1 700 1 550	2 470	2 550					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		790	1 000 1 620 1 270	1 215 1 880 1 470 1 380 1 290	1 345 2 080 1 630 1 530 1 420	1 475 2 280 1 790 1 675 1 555	1 605 2 480 1 950 1 825 1 685	1 735 2 680 2 110 1 970 1 820	1 865 2 880 2 270 2 120 1 950	3 080	3 180					
10 km/h 30 km/h 40 km/h 50 km/h			1 110 870	1 280 1 010 940 870	1 420 1 120 1 040 960	1 555 1 225 1 145 1 050	1 695 1 335 1 245 1 140	1 835 1 440 1 350 1 230	1 970 1 550 1 450 1 320	2 110	2 180					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		590	740 1 190 930	890 1 370 1 080 1 010 920	985 1 520 1 195 1 120 1 015	1 080 1 665 1 310 1 225 1 110	1 175 1 815 1 430 1 335 1 210	1 270 1 960 1 545 1 440 1 305	1 365 2 110 1 660 1 550 1 400	2 255	2 330					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		705	870 1 380 1 080	1 030 1 590 1 250 1 170 1 090	1 140 1 760 1 385 1 295 1 200	1 250 1 930 1 520 1 420 1 315	1 365 2 100 1 660 1 550 1 425	1 475 2 275 1 795 1 675 1 540	1 585 2 445 1 930 1 800 1 650	2 615	2 700					

40 Dual: twin fitment use.

10: max speed 10 km/h (low torque).

30: use on the road up to a maximum speed of 30 km/h

40: use on the road up to a maximum speed of 40 km/h

50: use on the road up to a maximum speed of 50 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.

(4) For use on side slopes: add 0.4 bar.

(5) For heavy road use: add 0.4 bar.

(6) (7) For work at low torque only.



Characteristics of MICHELIN standard radial tyres MICHELIN AGRIBIB

Ø inches	Description	CAI	Tyre characteristics				Rim widths ⁽¹⁾ inches	Tube ⁽²⁾	75% internal volume liters	
			S mm	D mm	R' mm	R.C. mm				
28	16.9 R28 136A8/133B TL AGRIBIB	123856	450	1427	641	4240	DW15L W14L DW14L W15L	822	271	
30	16.9 R30 137A8/134B TL AGRIBIB	123870	447	1480	664	4395	DW15L W14L DW14L W15L	754	285	
	18.4 R30 142A8/139B TL AGRIBIB	123844	504	1550	695	4602	DW16L W15L DW15L W16L	757	352	
	380/85 R30 135A8/135B TL AGRIBIB (14,9 R30)	836509	386	1416	628	4194	W12 W13	734	209	
	420/90 R30 147A8/147B TL AGRIBIB	953332	443	1533	690	4556	DW13 W13 W14L DW14L	754	284	
34	18.4 R34 144A8/141B TL AGRIBIB	123846	477	1662	744	4933	DW16L W15L DW15L W16L	823	395	
	320/85 R34 133A8/130B TL AGRIBIB (12,4 R34)	122760	320	1420	651	4239	W10	/	155	
	380/85 R34 137A8/137B TL AGRIBIB (14,9 R34)	122781	394	1503	673	4461	W12 W13	704	230	
	420/85 R34 142A8/142B TL AGRIBIB (16,9 R34)	042716	449	1580	707	4690	DW15L W13 W14L - DW14L W15L	704	287	

(1) The reference rim is shown in bold type.

(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015). Technical data are subject to change without prior notice.



From 60 to 170 HP*

(dependant on tyre size)

*** And up to 500 HP with twin wheels
(42", 46", 50")**



Pressure (bar) and (psi) - Load per tyre in kg ⁽³⁾ - (4) - (5)																
	Bar Psi	0,40 ⁽⁶⁾ 6	0,50 ⁽⁷⁾ 7	0,60 9	0,80 12	1,00 15	1,20 17	1,40 20	1,60 23	1,80 26	1,90 28	2,00 29	2,20 32	2,40 35	2,60 38	2,80 41
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		860 1 070 1 340	1 070 1 710 1 340	1 285 1 980 1 560 1 460 1 360	1 420 2 190 1 730 1 615 1 500	1 560 2 405 1 895 1 770 1 640	1 695 2 615 2 065 1 930 1 780	1 835 2 830 2 230 2 085 1 920	1 970 3 040 2 400 2 240 2 060	3 255 3 360						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		880 1 100 1 380	1 100 1 760 1 380	1 320 2 040 1 600 1 500 1 400	1 460 2 255 1 770 1 660 1 545	1 600 2 475 1 945 1 820 1 690	1 745 2 690 2 115 1 980 1 830	1 885 2 910 2 290 2 140 1 975	2 025 3 125 2 460 2 300 2 120	3 340 3 450						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 040 1 280 2 030 1 590	1 280 2 030 1 590	1 515 2 350 1 840 1 720 1 600	1 680 2 600 2 040 1 905 1 765	1 840 2 850 2 240 2 090 1 930	2 005 3 100 2 440 2 280 2 100	2 165 3 355 2 640 2 465 2 265	2 330 3 605 2 840 2 650 2 430	3 855 3 980						
40 km/h Dual 10 km/h 30 km/h 50 km/h		860 1 450 1 060	950 1 565 1 155	1 040 1 680 1 250 1 180	1 195 1 905 1 450 1 360	1 370 2 130 1 675 1 550	1 540 2 360 1 900 1 750	1 730 2 580 2 100 1 965	1 920 2 800 2 300 2 180	3 100 3 250						
40 km/h Dual 10 km/h 30 km/h 50 km/h		1 070 1 800 1 285	1 170 1 955 1 420	1 275 2 110 1 550 1 450	1 495 2 415 1 800 1 700	1 705 2 725 2 050 1 940	1 910 3 035 2 300 2 175	2 120 3 340 2 550 2 410	2 330 3 650 2 800 2 650	2 440 3 950 2 940 2 775	2 495 4 100 3 005 2 840	2 550 4 250 3 075 2 900	2 630 4 375 3 210 2 990	2 705 4 500 3 350 3 075	4 560	4 625
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 130 2 140 1 680	1 365 2 480 1 950 1 820 1 700	1 600 2 480 1 950 1 820 1 700	1 775 2 745 2 160 2 015 1 875	1 945 3 010 2 370 2 210 2 050	2 120 3 275 2 580 2 410 2 230	2 290 3 540 2 790 2 605 2 405	2 465 3 805 3 000 2 800 2 580	4 070 4 200						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		705 1 215 850	780 1 315 940	860 1 410 1 030 975 900	985 1 610 1 215 1 120 1 030	1 130 1 805 1 380 1 285 1 180	1 275 2 000 1 550 1 450 1 320	1 410 2 215 1 725 1 600 1 460	1 540 2 430 1 900 1 750 1 600	1 630 2 615 1 980 1 850 1 700	1 670 2 710 2 020 1 900 1 750	1 715 2 800 2 060 1 950 1 800	1 765 2 870 2 120 2 005 1 850	1 815 2 940 2 180 2 060 1 900	3 005	3 075
40 km/h Dual 10 km/h 30 km/h 50 km/h		905 1 550 1 120	1 000 1 670 1 220	1 100 1 790 1 320 1 250	1 275 2 025 1 550 1 450	1 450 2 260 1 775 1 650	1 630 2 500 2 000 1 850	1 830 2 750 2 215 2 075	2 025 3 000 2 430 2 300	3 300 3 450						
40 km/h Dual 10 km/h 30 km/h 50 km/h		1 070 1 800 1 300	1 175 1 940 1 430	1 280 2 075 1 555 1 450	1 490 2 350 1 810 1 690	1 700 2 625 2 070 1 930	1 910 2 900 2 325 2 170	2 120 3 175 2 580 2 410	2 330 3 450 2 835 2 650	3 800 3 975						

40 Dual: twin fitment use.

10: max speed 10 km/h (low torque).

30: use on the road up to a maximum speed of 30 km/h

40: use on the road up to a maximum speed of 40 km/h

50: use on the road up to a maximum speed of 50 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.

(4) For use on side slopes: add 0.4 bar.

(5) For heavy road use: add 0.4 bar.

(6) (7) For work at low torque only.



Characteristics of MICHELIN standard radial tyres MICHELIN AGRIBIB

Ø inches	Description	CAI	Tyre characteristics				Rim widths ⁽¹⁾ inches	Tube ⁽²⁾	75% internal volume liters	
			S mm	D mm	R' mm	R.C. mm				
36	12.4 R36 124A8/121B TL AGRIBIB	123952	318	1460	673	4363	W11 W10	779	165	
38	12.4 R38 125A8/122B TL AGRIBIB	123962	311	1500	691	4481	W11 W10 DW10	779	165	
	13.6 R38 128A8/125B TL AGRIBIB	123992	358	1565	722	4705	DW12 W11 W12	795	217	
	18.4 R38 146A8/143B TL AGRIBIB	122771	491	1770	795	5258	DW16L W15L DW15L W16L	824	431	
	20.8 R38 153A8/150B TL AGRIBIB	123860	541	1844	823	5470	DW18L W16L DW16L W18L	825	523	
	380/80 R38 142A8/139D TL AGRIBIB	667404	380	1578	723	4709	DW12A W12 DW12 W13 DW13	795 796	230	
	380/80 R38 142A8/142B TL AGRIBIB	051026	380	1578	723	4709	DW12A W12 DW12 W13 DW13	795 796	230	
	380/95 R38 147A8/147B TL AGRIBIB *	836033	393	1687	764	5021	W12 W13	795	285	

(1) La jante de référence est indiquée en caractères gras.

(2) Codes chambres à air Kléber.

* En cours de développement. Nous consulter pour disponibilités

IMPORTANT : La pression de gonflage se détermine toujours en fonction de la charge par pneu, de la vitesse et du travail à réaliser.

Nos préconisations ci-dessus sont fournies sous réserve de modifications postérieures à la date de diffusion de ces tableaux (March 2015)

Les données techniques sont susceptibles d'évoluer sans information préalable.



From 60 to 170 HP*

(dependant on tyre size)

* And up to 500 HP with twin wheels
(42", 46", 50")



Pressure (bar) and (psi) - Load per tyre in kg ⁽³⁾ - (4) - (5)																
	Bar Psi	0,40 ⁽⁶⁾ 6	0,50 ⁽⁷⁾ 7	0,60 9	0,80 12	1,00 15	1,20 17	1,40 20	1,60 23	1,80 26	1,90 28	2,00 29	2,20 32	2,40 35	2,60 38	2,80 41
10 km/h 30 km/h 40 km/h 50 km/h			1 220 960	1 420 1 110 1 040 960	1 570 1 230 1 150 1 060	1 720 1 350 1 265 1 155	1 870 1 470 1 375 1 255	2 025 1 590 1 490 1 350	2 175 1 710 1 600 1 450	2 325	2 400					
10 km/h 30 km/h 40 km/h 50 km/h			1 260 990	1 460 1 150 1 070 990	1 615 1 275 1 185 1 090	1 775 1 400 1 300 1 195	1 930 1 520 1 420 1 295	2 090 1 645 1 535 1 400	2 245 1 770 1 650 1 500	2 400	2 480					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		685	860 1 380 1 080	1 030 1 590 1 250 1 170 1 090	1 140 1 760 1 385 1 295 1 200	1 250 1 930 1 520 1 420 1 315	1 365 2 100 1 660 1 550 1 425	1 475 2 275 1 795 1 675 1 540	1 585 2 445 1 930 1 800 1 650	2 615	2 700					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 195	1 455 2 300 1 800	1 715 2 660 2 090 1 950 1 800	1 900 2 945 2 315 2 160 1 985	2 085 3 225 2 540 2 370 2 170	2 270 3 510 2 760 2 580 2 360	2 455 3 790 2 985 2 790 2 545	2 640 4 075 3 210 3 000 2 730	4 360	4 500					
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 450	1 770 2 790 2 190	2 085 3 230 2 540 2 370 2 210	2 310 3 575 2 815 2 625 2 440	2 535 3 920 3 090 2 880 2 665	2 760 4 270 3 360 3 140 2 895	2 985 4 615 3 635 3 395 3 120	3 210 4 960 3 910 3 650 3 350	5 305	5 480					
40 km/h Dual 10 km/h 30 km/h 40 km/h 65 km/h		905 1 545 1 100	1 000 1 680 1 215	1 090 1 815 1 325 1 250 975	1 280 2 085 1 555 1 460 1 130	1 465 2 360 1 780 1 670 1 285	1 650 2 630 2 005 1 880 1 440	1 840 2 900 2 235 2 090 1 595	2 025 3 170 2 460 2 300 1 750	2 100 3 345 2 555 2 390 1 920	2 140 3 435 2 600 2 430 2 005	2 180 3 520 2 650 2 475 2 090	2 255 3 700 2 740 2 560 2 260	2 330 3 875 2 835 2 650 2 430	3 940	4 000
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		905 1 545 1 100	1 000 1 680 1 215	1 090 1 815 1 325 1 250 1 250	1 280 2 085 1 555 1 460 1 460	1 465 2 360 1 780 1 670 1 670	1 650 2 630 2 005 1 880 1 880	1 840 2 900 2 235 2 090 2 090	2 025 3 170 2 460 2 300 2 300	2 100 3 345 2 555 2 390 2 390	2 140 3 435 2 600 2 430 2 430	2 180 3 520 2 650 2 475 2 475	2 255 3 700 2 740 2 560 2 560	2 330 3 875 2 835 2 650 2 650	3 940	4 000
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 070 1 300 1 300 1 215 1 215	1 175 1 490 1 430 1 335 1 335	1 280 1 680 1 555 1 455 1 455	1 490 2 065 1 810 1 695 1 695	1 700 2 445 2 070 1 930 1 930	1 910 2 830 2 325 2 170 2 170	2 120 3 210 2 580 2 410 2 410	2 330 3 595 2 835 2 650 2 650	2 425 3 975 2 950 2 755 2 755	2 470 4 040 3 005 2 810 2 810	2 520 4 100 3 060 2 860 2 860	2 610 4 230 3 175 2 970 2 970	2 705 4 355 3 290 3 075 3 075	4 485	4 610

40 Dual : utilisation en jumelé.

10 : vitesse maxi 10km/h sans couple élevé et soutenu.

30 : utilisation sur route jusqu'à 30 km/h.

40 : utilisation sur route jusqu'à 40 km/h.

50 : utilisation sur route jusqu'à 50 km/h.

(3) Pour usage champ sous couple (ex: labour), utiliser la ligne 30 km/h.

(4) Pour usage en dévers : ajouter 0,40 bar.

(5) Pour usage routier intensif : ajouter 0,40 bar.

(6) (7) Uniquement pour travaux sans couple.



Characteristics of MICHELIN standard radial tyres MICHELIN AGRIBIB

Ø inches	Description	CAI	Tyre characteristics				Rim widths ⁽¹⁾ inches	Tube ⁽²⁾	75% internal volume liters	
			S mm	D mm	R' mm	R.C. mm				
38	420/85 R38 144A8/144B TL AGRIBIB (16,9 R38)	607820	455	1676	750	4975	DW15L W14L DW14L W15L	786	311	
	520/85 R38 155A8/155B TL AGRIBIB (20,8 R38)	303668	530	1855	821	5529	DW16L W16A DD16 W18A DD18	825	508	
42	480/80 R42 156A8/156B TL AGRIBIB (18,4 R42)	404096	494	1858	847	5538	DW16A W16A DD16	801	420	
	520/85 R42 157A8/157B TL AGRIBIB (20,8 R42)	122791	539	1945	869	5771	DW18A W18A DD18	802	544	
46	420/80 R46 151A8/148B TL AGRIBIB	122770	410	1872	861	5555	DW13	835	333	
	480/80 R46 158A8/158B TL AGRIBIB (18,4 R46)	637231	499	1948	889	5874	DW16A W16A DD16 DW16L	834	449	
	520/85 R46 158A8/155B TL AGRIBIB (20,8 R46)	122780	515	2050	920	6088	DW16A W16A, W16L DW16L, W18L DW18L, W18A DW18A	834	581	
50	480/80 R50 159A8/159B TL AGRIBIB	471947	474	2056	942	6135	DW15A DW16A	/	479	
	480/95 R50 164A8/164B TL	491183	515	2175	992	6484	DW16B (A) DW15B (A)	/	593	

(1) The reference rim is shown in bold type.
(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done.

Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015). Technical data are subject to change without prior notice.



From 60 to 170 HP*

(dependant on tyre size)

* And up to 500 HP with twin wheels
(42", 46", 50")



Pressure (bar) and (psi) - Load per tyre in kg ⁽³⁾ - (4) - (5)																
	Bar Psi	0,40 ⁽⁶⁾ 6	0,50 ⁽⁷⁾ 7	0,60 9	0,80 12	1,00 15	1,20 17	1,40 20	1,60 23	1,80 26	1,90 28	2,00 29	2,20 32	2,40 35	2,60 38	2,80 41
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 130 1 900 1 375	1 240 2 045 1 510	1 350 2 190 1 645 1 550 1 550	1 575 2 485 1 915 1 800 1 800	1 800 2 775 2 190 2 050 2 050	2 020 3 065 2 460 2 300 2 300	2 240 3 360 2 730 2 550 2 550	2 465 3 650 3 000 2 800 2 800	4 015 4 200						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 540 2 650 1 900	1 700 2 850 2 100	1 865 3 050 2 300 2 120 2 120	2 200 3 450 2 650 2 500 2 500	2 485 3 850 3 050 2 825 2 800	2 770 4 250 3 450 3 150 3 160	3 090 4 625 3 790 3 510 3 515	3 410 5 000 4 125 3 875 3 875	5 535 5 800						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 320 2 325 1 660	1 465 2 505 1 830	1 605 2 690 2 000 1 850 1 850	1 890 3 050 2 335 2 170 2 170	2 180 3 410 2 675 2 490 2 490	2 465 3 775 3 015 2 810 2 810	2 750 4 140 3 350 3 130 3 130	3 035 4 500 3 690 3 450 3 450	3 155 4 750 3 840 3 590 3 590	3 215 4 875 3 910 3 655 3 655	3 280 5 000 3 985 3 725 3 725	3 400 5 250 4 130 3 860 3 860	3 520 5 500 4 280 4 000 4 000	5 750	6 000
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 630 2 800 2 000	1 800 3 010 2 180	1 970 3 225 2 360 2 240 2 240	2 265 3 650 2 800 2 575 2 575	2 610 4 075 3 175 2 960 3 000	2 950 4 500 3 550 3 350 3 350	3 290 4 900 3 960 3 740 3 740	3 630 5 300 4 375 4 125 4 125	5 865 6 150						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 160 2 000 1 450	1 285 2 170 1 575	1 410 2 340 1 700 1 600 1 450	1 630 2 675 2 000 1 850 1 700	1 885 3 010 2 290 2 140 1 950	2 140 3 350 2 575 2 430 2 240	2 345 3 675 2 860 2 665 2 445	2 550 4 000 3 150 2 900 2 650	2 705 4 310 3 300 3 075 2 800	2 780 4 470 3 375 3 160 2 900	2 860 4 625 3 450 3 250 3 000	2 950 4 810 3 550 3 350 3 075	3 035 5 000 3 650 3 450 3 150	5 075	5 150
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 450 2 475 1 770	1 580 2 675 1 940	1 715 2 875 2 110 1 950 1 950	1 940 3 275 2 445 2 270 2 270	2 165 3 675 2 785 2 590 2 590	2 390 4 075 3 125 2 910 2 910	2 615 4 475 3 460 3 230 3 230	2 840 4 875 3 800 3 550 3 550	3 065 5 125 3 990 3 725 3 725	3 180 5 250 4 080 3 810 3 810	3 290 5 375 4 175 3 900 3 900	3 515 5 630 4 360 4 075 4 075	3 740 5 880 4 550 4 250 4 250	6 130	6 380
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 715 2 900 2 090	1 885 3 110 2 295	2 050 3 325 2 500 2 300 2 120	2 390 3 750 2 910 2 690 2 470	2 730 4 175 3 320 3 080 2 820	3 065 4 600 3 730 3 470 3 175	3 400 5 025 4 140 3 860 3 525	3 740 5 450 4 550 4 250 3 875	6 070 6 380						
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 495 2 575 1 800	1 655 2 785 1 990	1 815 2 995 2 180 2 060 2 060	2 075 3 410 2 575 2 360 2 360	2 390 3 830 2 910 2 720 2 725	2 705 4 250 3 250 3 075 3 075	3 000 4 700 3 625 3 410 3 410	3 300 5 150 4 000 3 750 3 750	3 465 5 575 4 190 3 940 3 875	3 550 5 790 4 280 4 030 4 000	3 630 6 000 4 375 4 125 4 125	3 740 6 150 4 500 4 250 4 250	3 850 6 300 4 625 4 375 4 375	6 400	6 500
40 km/h Dual 10 km/h 30 km/h 40 km/h 50 km/h		1 720 2 925 2 085	1 900 3 100 2 305	2 080 3 270 2 525 2 360 2 360	2 435 3 780 2 955 2 765 2 765	2 790 4 285 3 385 3 165 3 165	3 140 4 795 3 820 3 570 3 570	3 495 5 300 4 250 3 970 3 970	3 850 5 810 4 680 4 375 4 375	3 990 6 185 4 850 4 530 4 530	4 055 6 370 4 930 4 610 4 610	4 125 6 560 5 015 4 690 4 690	4 260 6 935 5 180 4 845 4 845	4 400 7 310 5 350 5 000 5 000	7 405	7 500

40 Dual: twin fitment use.

10: max speed 10 km/h (low torque).

30: use on the road up to a maximum speed of 30 km/h

40: use on the road up to a maximum speed of 40 km/h

50: use on the road up to a maximum speed of 50 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.

(4) For use on side slopes: add 0.4 bar.

(5) For heavy road use: add 0.4 bar.

(6) (7) For work at low torque only.

