Great versatility to optimise your operations

MICHELIN OMNIBIB

Versatility

Service life

Versatility

- Specially designed to withstand the stresses of work with front loaders
- Excellent stability and manoeuvrability for work in animal stalls
- Super towing performance

Service life

- Proven casing endurance and damage resistance

Up to 14% more load capacity than a standard tyre (depending on tyre sizes and compared with the equivalent size in the MICHELIN Agribib range)

From 70 to 180 HP

(dependant on tyre size)

Wide lugs

- Longer service life

Flexible, robust casing

Wide, flat tread

- Greater stability

Sizes		
320/70 R24 TL 116D	380/70 R28 TL 127D	480/70 R38 TL 145D
360/70 R24 TL 122D	420/70 R28 TL 133D	520/70 R38 TL 150D
380/70 R24 TL 125D	480/70 R28 TL 140D	580/70 R38 TL 155D
420/70 R24 TL 130D	480/70 R30 TL 141D	620/70 R42 TL 160D
480/70 R24 TL 138D	480/70 R34 TL 143D	
360/70 R28 TL 125D	520/70 R34 TL 148D	

MICHELIN
A better way forward

Characteristics of MICHELIN 70 series wide tyres MICHELIN OMNIBIB

Ø	Description	CAI	Tyre characteristics				Rim widths (1)	Tube (2)	75% internal volume
			S	D	R'	R.C.			
inches			mm	mm	mm	mm	inches		liters
24	320/70 R24 116D TL OMNIBIB	415039	323	1101	497	3274	**W10** W11 W9	692	93
	360/70 R24 122D TL OMNIBIB	198698	373	1153	513	3418	**W11** W12 W10	692	136
	380/70 R24 125D TL OMNIBIB	085816	399	1188	528	3520	**W12** W11 W13	700	160
	420/70 R24 130D TL OMNIBIB	829095	436	1251	553	3702	**W13** W12 W14L DW14L	703	203
	480/70 R24 138D TL OMNIBIB	375821	494	1327	578	3916	**DW15L** W14L DW14L W16L W15L DW16L	710	276

(1) The reference rim is shown in bold type.
(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015) Technical data are subject to change without prior notice.

From 70 to 180 HP

(dependant on tyre size)

Pressure (bar) and (psi) - Load per tyre in kg [3] - [4] - [5]

Bar / *Psi*	0,40 [6] *6*	0,50 [7] *7*	0,60 *9*	0,70 *10*	0,80 *12*	0,90 *13*	1,00 *15*	1,20 *17*	1,40 *20*	1,50 *22*	1,60 *23*	1,70 *25*	1,80 *26*	1,90 *28*	2,00 *29*
40 km/h Dual	560	615	670	720	775	830	880	990	1 100	1 150	1 205				
10 km/h	870	935	995	1 060	1 120	1 185	1 250	1 375	1 500	1 565	1 630	1 690	1 755	1 815	1 880
30 km/h	670	735	800	860	925	990	1 055	1 185	1 310	1 375	1 440				
40 km/h			760	820	880	945	1 005	1 125	1 250	1 310	1 370				
50 km/h			720	780	840	895	955	1 075	1 190	1 250	1 310				
65 km/h			690	745	800	860	915	1 025	1 140	1 195	1 250				
40 km/h Dual	665	730	795	860	925	990	1 055	1 185	1 315	1 380	1 445				
10 km/h	1 040	1 115	1 190	1 265	1 340	1 420	1 495	1 645	1 795	1 870	1 950	2 025	2 100	2 175	2 250
30 km/h	790	870	945	1 025	1 105	1 180	1 260	1 415	1 575	1 650	1 730				
40 km/h			900	975	1 050	1 120	1 195	1 345	1 490	1 565	1 640				
50 km/h			870	940	1 010	1 085	1 155	1 295	1 440	1 510	1 580				
65 km/h			825	890	960	1 030	1 095	1 230	1 365	1 430	1 500				
40 km/h Dual	725	795	865	940	1 010	1 080	1 155	1 300	1 445	1 520	1 590				
10 km/h	1 130	1 215	1 300	1 385	1 470	1 550	1 635	1 805	1 975	2 060	2 140	2 225	2 310	2 395	2 480
30 km/h	860	945	1 035	1 120	1 205	1 295	1 380	1 555	1 725	1 815	1 900				
40 km/h			990	1 070	1 155	1 235	1 320	1 480	1 645	1 730	1 810				
50 km/h			950	1 030	1 105	1 185	1 260	1 420	1 575	1 650	1 730				
65 km/h			900	975	1 050	1 125	1 200	1 350	1 500	1 575	1 650				
40 km/h Dual	845	920	995	1 080	1 160	1 245	1 330	1 495	1 665	1 745	1 830				
10 km/h	1 310	1 405	1 500	1 600	1 695	1 790	1 890	2 080	2 270	2 370	2 465	2 560	2 660	2 755	2 850
30 km/h	1 010	1 110	1 205	1 305	1 405	1 500	1 600	1 795	1 995	2 090	2 190				
40 km/h			1 130	1 225	1 320	1 415	1 510	1 700	1 890	1 985	2 080				
50 km/h			1 080	1 170	1 265	1 355	1 450	1 630	1 815	1 910	2 000				
65 km/h			1 030	1 115	1 205	1 290	1 380	1 550	1 725	1 815	1 900				
40 km/h Dual	1 020	1 130	1 240	1 345	1 445	1 550	1 655	1 860	2 070	2 170	2 275				
10 km/h	1 590	1 710	1 835	1 955	2 080	2 200	2 320	2 565	2 810	2 930	3 050	3 175	3 295	3 420	3 540
30 km/h	1 220	1 345	1 470	1 590	1 715	1 840	1 965	2 215	2 460	2 585	2 710				
40 km/h			1 410	1 525	1 645	1 760	1 880	2 110	2 345	2 465	2 580				
50 km/h			1 350	1 465	1 575	1 690	1 800	2 030	2 255	2 365	2 480				
65 km/h			1 285	1 390	1 500	1 610	1 715	1 930	2 145	2 250	2 360				

40 Dual: twin fitment use.
10: max speed 10 km/h (low torque).
30: use on the road up to a maximum speed of 30 km/h
40: use on the road up to a maximum speed of 40 km/h
50: use on the road up to a maximum speed of 50 km/h
65: use on the road up to a maximum speed of 65 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.
(4) For use on side slopes: add 0.4 bar.
(5) For heavy road use: add 0.4 bar.
(6) (7) For work at low torque only.

MICHELIN
A better way forward

Characteristics of MICHELIN 70 series wide tyres MICHELIN OMNIBIB

Ø	Description	CAI	Tyre characteristics				Rim widths (1)	Tube (2)	75% internal volume
			S	D	R'	R.C.			
inches			mm	mm	mm	mm	inches		liters
28	360/70 R28 125D TL OMNIBIB	534919	372	1260	562	3737	**W11** W10 W12	726	153
	380/70 R28 127D TL OMNIBIB	118587	390	1294	580	3842	**W12** W13 W11	732	179
	420/70 R28 133D TL OMNIBIB	532215	436	1354	602	4012	**W13** W12 DW14L W14L	821	223
	480/70 R28 140D TL OMNIBIB	570026	500	1423	632	4217	**DW15L** DW14L W16L W15L W14L DW16L	822	301
30	480/70 R30 141D TL OMNIBIB	599351	498	1482	656	4388	**DW15L** DW14L W14L W16L W15L DW16L	754	316
34	480/70 R34 143D TL OMNIBIB	280033	497	1593	713	4728	**DW15L** W14L DW14L W15L W16L DW16L	704	345
	520/70 R34 148D TL OMNIBIB	939411	535	1651	730	4887	**DW16L** DW18L W18L W16L DW15L W15L	823	421

(1) The reference rim is shown in bold type.
(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015) Technical data are subject to change without prior notice.

From 70 to 180 HP

(dependant on tyre size)

Pressure (bar) and (psi) - Load per tyre in kg [3] - [4] - [5]

Bar / *Psi*	0,40 [6] / *6*	0,50 [7] / *7*	0,60 / *9*	0,70 / *10*	0,80 / *12*	0,90 / *13*	1,00 / *15*	1,20 / *17*	1,40 / *20*	1,50 / *22*	1,60 / *23*	1,70 / *25*	1,80 / *26*	1,90 / *28*	2,00 / *29*
40 km/h Dual	705	775	845	920	995	1 070	1 145	1 290	1 440	1 515	1 590				
10 km/h	1 100	1 185	1 270	1 360	1 445	1 530	1 620	1 790	1 960	2 050	2 135	2 220	2 310	2 395	2 480
30 km/h	840	930	1 015	1 105	1 195	1 280	1 370	1 545	1 725	1 810	1 900				
40 km/h			960	1 045	1 130	1 215	1 300	1 470	1 640	1 725	1 810				
50 km/h			920	1 000	1 080	1 165	1 245	1 405	1 570	1 650	1 730				
65 km/h			875	950	1 030	1 110	1 185	1 340	1 495	1 570	1 650				
40 km/h Dual	770	840	915	990	1 070	1 145	1 225	1 375	1 530	1 610	1 685				
10 km/h	1 200	1 290	1 380	1 470	1 560	1 645	1 735	1 915	2 095	2 185	2 270	2 360	2 450	2 540	2 630
30 km/h	920	1 010	1 100	1 190	1 285	1 375	1 465	1 645	1 830	1 920	2 010				
40 km/h			1 040	1 130	1 215	1 305	1 390	1 570	1 745	1 830	1 920				
50 km/h			1 000	1 085	1 170	1 250	1 335	1 505	1 670	1 755	1 840				
65 km/h			950	1 030	1 110	1 190	1 270	1 430	1 590	1 670	1 750				
40 km/h Dual	890	985	1 080	1 170	1 260	1 350	1 440	1 625	1 805	1 895	1 985				
10 km/h	1 390	1 495	1 600	1 710	1 815	1 920	2 030	2 240	2 450	2 560	2 665	2 770	2 880	2 985	3 090
30 km/h	1 060	1 170	1 280	1 390	1 495	1 605	1 715	1 935	2 150	2 260	2 370				
40 km/h			1 230	1 335	1 435	1 540	1 640	1 850	2 055	2 155	2 260				
50 km/h			1 180	1 280	1 375	1 475	1 570	1 770	1 965	2 060	2 160				
65 km/h			1 120	1 215	1 310	1 400	1 495	1 685	1 870	1 965	2 060				
40 km/h Dual	1 110	1 210	1 310	1 420	1 530	1 640	1 750	1 970	2 190	2 300	2 410				
10 km/h	1 730	1 855	1 980	2 110	2 235	2 360	2 490	2 740	2 990	3 120	3 245	3 370	3 500	3 625	3 750
30 km/h	1 320	1 450	1 580	1 710	1 840	1 970	2 100	2 360	2 620	2 750	2 880				
40 km/h			1 490	1 615	1 740	1 865	1 990	2 240	2 490	2 615	2 740				
50 km/h			1 430	1 550	1 670	1 790	1 910	2 150	2 390	2 510	2 630				
65 km/h			1 360	1 475	1 590	1 700	1 815	2 045	2 270	2 385	2 500				
40 km/h Dual	1 135	1 240	1 350	1 465	1 575	1 690	1 800	2 030	2 255	2 365	2 480				
10 km/h	1 770	1 900	2 030	2 160	2 290	2 425	2 555	2 815	3 075	3 205	3 340	3 470	3 600	3 730	3 860
30 km/h	1 360	1 495	1 625	1 760	1 895	2 025	2 160	2 425	2 695	2 825	2 960				
40 km/h			1 530	1 660	1 790	1 915	2 045	2 305	2 560	2 690	2 820				
50 km/h			1 470	1 595	1 715	1 840	1 960	2 210	2 455	2 575	2 700				
65 km/h			1 400	1 520	1 635	1 750	1 870	2 105	2 340	2 460	2 575				
40 km/h Dual	1 205	1 325	1 445	1 565	1 680	1 800	1 915	2 155	2 390	2 505	2 625				
10 km/h	1 880	2 020	2 155	2 295	2 430	2 570	2 710	2 985	3 260	3 400	3 540	3 675	3 815	3 950	4 090
30 km/h	1 440	1 580	1 720	1 860	2 005	2 145	2 285	2 565	2 850	2 990	3 130				
40 km/h			1 640	1 775	1 910	2 040	2 175	2 445	2 710	2 845	2 980				
50 km/h			1 580	1 710	1 835	1 965	2 090	2 350	2 605	2 730	2 860				
65 km/h			1 500	1 620	1 745	1 870	1 990	2 235	2 480	2 600	2 725				
40 km/h Dual	1 350	1 495	1 640	1 780	1 920	2 060	2 200	2 475	2 755	2 895	3 035				
10 km/h	2 100	2 265	2 430	2 595	2 760	2 920	3 085	3 415	3 745	3 910	4 070	4 235	4 400	4 565	4 730
30 km/h	1 610	1 780	1 945	2 110	2 280	2 450	2 615	2 950	3 285	3 450	3 620				
40 km/h			1 860	2 020	2 180	2 335	2 495	2 815	3 130	3 290	3 450				
50 km/h			1 790	1 940	2 095	2 245	2 400	2 700	3 005	3 160	3 310				
65 km/h			1 700	1 845	1 990	2 135	2 280	2 570	2 860	3 005	3 150				

40 Dual: twin fitment use.
10: max speed 10 km/h (low torque).
30: use on the road up to a maximum speed of 30 km/h
40: use on the road up to a maximum speed of 40 km/h
50: use on the road up to a maximum speed of 50 km/h
65: use on the road up to a maximum speed of 65 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.
(4) For use on side slopes: add 0.4 bar.
(5) For heavy road use: add 0.4 bar.
(6) (7) For work at low torque only.

MICHELIN
A better way forward

Characteristics of MICHELIN 70 series wide tyres MICHELIN OMNIBIB

Ø	Description	CAI	Tyre characteristics				Rim widths (1)	Tube (2)	75% internal volume
			S	D	R'	R.C.			
inches			mm	mm	mm	mm	inches		liters
38	480/70 R38 145D TL OMNIBIB	936570	498	1694	759	5030	**DW15L** DW16L W15L DW14L W16L W14L	786	377
	520/70 R38 150D TL OMNIBIB	833744	539	1766	782	5229	**DW16L** W15L W18L DW18L W16L DW15L	824	463
	580/70 R38 155D TL OMNIBIB	001240	601	1836	815	5440	**DW18L** W18L	825	589
42	620/70 R42 160D TL OMNIBIB	989457	639	1953	863	5781	**DW20B (A)** DW18L	802	657

(1) The reference rim is shown in bold type.
(2) Kleber tube code.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015) Technical data are subject to change without prior notice.

From 70 to 180 HP

(dependant on tyre size)

Pressure (bar) and (psi) - Load per tyre in kg [3] - [4] - [5]

Bar / *Psi*	0,40 [6] / *6*	0,50 [7] / *7*	0,60 / *9*	0,70 / *10*	0,80 / *12*	0,90 / *13*	1,00 / *15*	1,20 / *17*	1,40 / *20*	1,50 / *22*	1,60 / *23*	1,70 / *25*	1,80 / *26*	1,90 / *28*	2,00 / *29*
40 km/h Dual	1 270	1 405	1 540	1 665	1 790	1 915	2 040	2 295	2 545	2 670	2 795				
10 km/h	1 980	2 130	2 275	2 425	2 570	2 720	2 870	3 165	3 460	3 610	3 760	3 905	4 055	4 200	4 350
30 km/h	1 520	1 670	1 825	1 975	2 125	2 280	2 430	2 735	3 035	3 190	3 340				
40 km/h			1 750	1 895	2 035	2 180	2 320	2 610	2 895	3 035	3 180				
50 km/h			1 680	1 815	1 955	2 090	2 230	2 500	2 775	2 915	3 050				
65 km/h			1 600	1 730	1 860	1 990	2 120	2 380	2 640	2 770	2 900				
40 km/h Dual	1 445	1 590	1 735	1 885	2 035	2 185	2 335	2 630	2 930	3 080	3 230				
10 km/h	2 250	2 425	2 600	2 770	2 945	3 120	3 290	3 640	3 990	4 160	4 335	4 510	4 680	4 855	5 030
30 km/h	1 730	1 905	2 085	2 260	2 435	2 615	2 790	3 145	3 495	3 675	3 850				
40 km/h			1 970	2 140	2 310	2 480	2 650	2 990	3 330	3 500	3 670				
50 km/h			1 890	2 055	2 215	2 380	2 540	2 870	3 195	3 355	3 520				
65 km/h			1 800	1 955	2 110	2 265	2 420	2 730	3 040	3 195	3 350				
40 km/h Dual	1 685	1 865	2 045	2 215	2 385	2 550	2 720	3 060	3 395	3 565	3 735				
10 km/h	2 630	2 830	3 030	3 225	3 425	3 625	3 820	4 220	4 620	4 815	5 015	5 215	5 410	5 610	5 810
30 km/h	2 010	2 215	2 420	2 620	2 825	3 030	3 235	3 645	4 050	4 255	4 460				
40 km/h			2 320	2 510	2 705	2 895	3 090	3 470	3 855	4 050	4 240				
50 km/h			2 230	2 415	2 600	2 780	2 965	3 335	3 700	3 885	4 070				
65 km/h			2 120	2 295	2 470	2 645	2 820	3 175	3 525	3 700	3 875				
40 km/h Dual	1 985	2 160	2 340	2 540	2 740	2 940	3 140	3 535	3 935	4 135	4 335				
10 km/h	3 090	3 320	3 550	3 775	4 005	4 235	4 460	4 920	5 380	5 605	5 835	6 065	6 290	6 520	6 750
30 km/h	2 370	2 605	2 840	3 070	3 305	3 540	3 775	4 245	4 710	4 945	5 180				
40 km/h			2 660	2 885	3 115	3 340	3 570	4 020	4 475	4 705	4 930				
50 km/h			2 550	2 770	2 985	3 205	3 420	3 860	4 295	4 510	4 730				
65 km/h			2 430	2 635	2 845	3 050	3 260	3 670	4 085	4 295	4 500				

40 Dual: twin fitment use.
10: max speed 10 km/h (low torque).
30: use on the road up to a maximum speed of 30 km/h
40: use on the road up to a maximum speed of 40 km/h
50: use on the road up to a maximum speed of 50 km/h
65: use on the road up to a maximum speed of 65 km/h

(3) For ploughing and other applications subject to high torque use the 30 km/h row.
(4) For use on side slopes: add 0.4 bar.
(5) For heavy road use: add 0.4 bar.
(6) (7) For work at low torque only.

MICHELIN
A better way forward