

Excellent value  
for transporting your harvests

# MICHELIN

## CARGOXBIB HEAVY DUTY

NEW

Service life



Versatility



### Service life

- Proven casing endurance

### Versatility

- Reduces rutting
- Very good self-cleaning capacity
- Good handling on and off-road





## NEW TREAD PATTERN

### ■ Solid rounded shoulders

- Limits scrub when turning on grass
- Increases manoeuvrability
- Reduces shoulder wear.

### ■ Long-lasting casing

- Proven casing endurance
- High load capacity



### ■ New tread pattern

- Excellent self-cleaning capacity
- Even spread of ground pressure to minimise rutting and soil damage
- Better grip in difficult conditions
- Consistent, regular wear

### ■ Tread blocks + flat crown + larger footprint

- Even spread of ground pressure to minimise rutting

### Sizes

500/60 R22,5 TL 155D

NEW

560/45 R22,5 TL 152D

NEW

560/60 R22,5 TL 161D

NEW



# Characteristics of tyres for trailers and towed machinery

## MICHELIN CARGOXBIB HEAVY DUTY

Ø inches	Description	CAI	Tyre characteristics				Rim widths <sup>(1)</sup> inches	Tube <sup>(2)</sup>	75% internal volume litres
			S mm	D mm	R' mm	R.C. mm			
<b>22.5</b>	500/60 R22.5 155D TL CARGOXBIB HEAVY DUTY *	441880	500	1172	520	3472	<b>AG16.00 (H2)</b> 14.00 15.00 16.00 17.00	/	205
	560/45 R22.5 152D TL CARGOXBIB HEAVY DUTY *	743789	550	1076	483	3195	<b>AG16.00 (H2)</b>	/	182
	560/60 R22.5 161D TL CARGOXBIB HEAVY DUTY *	102433	543	1244	548	3679	<b>AG16.00 (H2)</b> 16.00 17.00 AG20.00 (H2)	/	268

(1) The reference rim is shown in bold type.

(2) Kleber tube code.

\* Under development. Ask us about available stock.

IMPORTANT: The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (March 2015). Technical data is subject to change without prior notice.



Pressure (bar) and (psi) - Load per tyre in kg<sup>(4)</sup>

Bar Psi	0,80 12	1,00 15	1,20 17	1,50 22	1,80 26	2,00 29	2,20 32	2,40 35	2,60 38	2,80 41	3,00 44	3,20 46	3,40 49	3,60 52	3,80 55	4,00 58
10 km/h	2 250	3 160	3 515	4 045	4 585	4 940	5 295	5 650	5 815	5 980	6 150	6 315	6 480	6 650	6 815	6 980
25 km/h	1 975	2 680	3 005	3 490	3 985	4 310	4 635	4 960	5 105	5 250	5 395	5 540	5 685	5 830	5 975	6 120
40 km/h	1 700	2 330	2 605	3 020	3 440	3 715	3 995	4 270	4 395	4 520	4 645	4 770	4 895	5 020	5 145	5 270
50 km/h	1 510	2 070	2 315	2 685	3 060	3 305	3 555	3 800	3 910	4 020	4 135	4 245	4 355	4 470	4 580	4 690
65 km/h	1 250	1 730	1 930	2 235	2 535	2 735	2 940	3 140	3 230	3 325	3 420	3 510	3 600	3 695	3 790	3 880
10 km/h	2 070	2 395	2 665	3 095	3 475	3 710	3 980	4 245	4 515	4 780	5 050	5 320	5 585	5 855	6 120	6 390
25 km/h	1 820	2 085	2 340	2 720	3 050	3 255	3 490	3 725	3 960	4 195	4 430	4 670	4 905	5 140	5 375	5 610
40 km/h	1 565	1 800	2 015	2 340	2 625	2 800	3 005	3 205	3 410	3 610	3 815	4 020	4 220	4 425	4 625	4 830
50 km/h	1 390	1 600	1 795	2 085	2 340	2 495	2 675	2 855	3 035	3 215	3 400	3 580	3 760	3 940	4 120	4 300
65 km/h	1 150	1 325	1 480	1 720	1 930	2 060	2 210	2 360	2 505	2 655	2 805	2 955	3 105	3 250	3 400	3 550
10 km/h	2 700	3 780	4 205	4 845	5 475	5 900	6 325	6 750	6 950	7 145	7 340	7 540	7 740	7 935	8 130	8 330
25 km/h	2 370	3 190	3 580	4 160	4 745	5 135	5 520	5 910	6 085	6 260	6 435	6 610	6 785	6 960	7 135	7 310
40 km/h	2 040	2 790	3 120	3 610	4 105	4 435	4 760	5 090	5 240	5 390	5 540	5 690	5 840	5 990	6 140	6 290
50 km/h	1 810	2 470	2 765	3 205	3 645	3 940	4 235	4 530	4 665	4 800	4 930	5 065	5 200	5 330	5 465	5 600
65 km/h	1 500	2 070	2 310	2 670	3 030	3 270	3 510	3 750	3 860	3 970	4 080	4 190	4 300	4 410	4 520	4 630

10: max. speed 10 km/h.

25: use on the road up to a maximum speed of 25 km/h

40: use on the road up to a maximum speed of 40 km/h

50: use on the road up to a maximum speed of 50 km/h

65: use on the road up to a maximum speed of 65 km/h

(4) For use on side slopes: add 0.4 bar.

