





MULTIBIB™

VERSATILE 65 SERIES WIDE TIRE
WITH LONG SERVICE LIFE



VERSATILITY

- Great performance in the field & on the road
- Fuel efficiency and wide contact patch for soil protection



PRODUCTIVITY

- Excellent traction to save time and fuel
- Capable of speeds of up to 40 mph¹
- Larger air chamber & footprint to carry heavier loads at lower pressures vs standard profile radials



LONG SERVICE LIFE

- Deepest tread depth vs. 4 main competitors²



COMFORT

- Excellent road handling and ride comfort



(1) When authorised by the laws in force in the country
(2) For 650/65 R42 size

SIZES

320/65 R16 107D TL
320/65 R18 109A8/106B TL XM108
340/65 R18 113A8/110B TL XM108
420/65 R20 125A8/125B TL XM108
440/65 R20 128D TL
420/65 R24 126A8/126B TL XM108
440/65 R24 128D TL

480/65 R24 133D TL
540/65 R24 140D TL
420/65 R28 135D TL
440/65 R28 131D TL
480/65 R28 136D TL
540/65 R28 142D TL
540/65 R30 143D TL

540/65 R34 145D TL
540/65 R34 152D TL
600/65 R34 151D TL
540/65 R38 147D TL
600/65 R38 153D TL
650/65 R38 157D TL
650/65 R42 158D TL

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
16		320/65 R16 107D TL										39517 (494658)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
11.8	32.6	14.5	96.5	W8	W10L, W8L, W9						17.1	17.2	37		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	1170	1280	1390	1675	1950	2240	2515	2800	3075	3220					
20 mph	1145	1255	1365	1585	1810	2030	2260	2480							
25 mph		1170	1280	1500	1710	1930	2150	2360							
30 mph		1125	1225	1435	1640	1850	2060	2260							
40 mph		1080	1180	1380	1565	1765	1960	2150							

Rim Size (inch)		Description										MSPN (CAI)			
18		320/65 R18 109A8/106B TL XM108										78520 (123898)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
12.2	34.4	15.3	102.1	W9	W10							16.9	35		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	880	1180	1475	1775	2070	2370	2670	2965	3265	3415					
20 mph	860	1100	1345	1565	1775	1995	2205	2425							
25 mph		1015	1255	1465	1665	1875	2070	2270							
30 mph		950	1145	1335	1520	1720	1905	2095							

Rim Size (inch)		Description										MSPN (CAI)			
18		340/65 R18 113A8/110B TL XM108										79647 (123888)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
12.6	35.9	16	107	W9	W10							20.1	37		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	990	1325	1655	1985	2315	2645	2985	3320	3650	3815					
20 mph	970	1235	1500	1740	1985	2225	2470	2710							
25 mph		1145	1390	1620	1850	2085	2315	2535							
30 mph		1060	1280	1490	1700	1920	2125	2335							

Rim Size (inch)		Description										MSPN (CAI)			
20		420/65 R20 125A8/125B TL XM108										86582 (122702)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
15.6	41.9	18.1	123.4	W11	W10, W12							37	45		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	2140	2515	2890	3360	3825	4300	4760	5235							
20 mph	1700	2040	2380	2765	3140	3525	3900								
25 mph		1830	2225	2580	2930	3285	3640								
30 mph		1830	2225	2460	2700	2930	3165	3405	3640						

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
20		440/65 R20 128D TL										15810 (675464)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
17.5	42.9	18.7	128.3	W14L	W13, W15L						22.8	41.5	56		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	2645	2855	3065	3460	3860	4255	4685	5105	5535	5745	5950				
20 mph	2030	2250	2470	2875	3275	3680	4125	4565							
25 mph			2360	2745	3120	3505	3925	4345							
30 mph			2260	2570	2890	3195	3680	4165							
40 mph			2150	2500	2845	3195	3585	3970							
25 mph Dual	1700	1885	2070	2415	2745	3085	3460	3825							

Rim Size (inch)		Description										MSPN (CAI)			
24		420/65 R24 126A8/126B TL XM108										77842 (122712)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
15.6	45.7	20	134.8	W11	W10, W12							39.6	47		
Psi	6	7	9	12	15	17	20	23	25	26	28	29	32	35	39
6 mph **	2185	2580	2975	3460	3935	4420	4905	5380							
20 mph	1740	2095	2445	2845	3230	3625	4010								
25 mph			1875	2295	2655	3020	3385	3750							
30 mph			1875	2295	2535	2780	3020	3265	3505	3625	3750				

Rim Size (inch)		Description										MSPN (CAI)			
24		440/65 R24 128D TL										04039 (426389)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
17.3	46.7	20.8	138.5	DW14L	DW13, DW15L, W13, W14L, W15L						22.8	47	56		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	2835	3020	3195	3650	4090	4540	4905	5280	5645	5820	6010				
20 mph	2160	2380	2600	3040	3485	3925	4245	4565							
25 mph			2490	2910	3330	3750	4045	4345							
30 mph			2380	2790	3185	3595	3880	4165							
40 mph			2270	2655	3030	3415	3695	3970							
25 mph Dual	1810	2005	2195	2555	2930	3295	3560	3825							

Rim Size (inch)		Description										MSPN (CAI)			
24		480/65 R24 133D TL										03176 (531721)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
19	48.8	21.5	144.4	DW15L	DW14L, W14L, W15L						24.6	57.6	58		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	3195	3470	3750	4235	4720	5205	5645	6075	6515	6725	6945				
20 mph	2470	2735	3000	3470	3955	4430	4830	5225							
25 mph			2845	3305	3770	4235	4610	4980							
30 mph			2735	3175	3615	4055	4410	4760							
40 mph			2600	3020	3440	3860	4200	4540							
25 mph Dual	2070	2295	2500	2910	3320	3725	4055	4385							

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
24		540/65 R24 140D TL										08801 (097057)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
20.9	51.7	22.6	152.5	DW16L	DW18L, W16L, W18L						28.0	75.8	61		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	3860	4135	4410	4995	5590	6175	6700	7220	7750	8005	8265				
20 mph	3000	3275	3550	4155	4775	5380	5865	6350							
25 mph			3375	3955	4530	5115	5580	6040							
30 mph			3240	3805	4355	4915	5355	5800							
40 mph			3085	3615	4145	4675	5095	5510							
25 mph Dual	2515	2745	2965	3470	3990	4495	4905	5315							

Rim Size (inch)		Description										MSPN (CAI)			
28		420/65 R28 135D TL										62700 (778211)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
15.4	48.7	22	144.9	W11	W12						21.7	46.8	56		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	2810	3110	3405	3770	4135	4495	4815	5125	5500	5690	5875	6240	6615	7065	7210
20 mph	2160	2390	2610	2985	3385	3780	4165	4565	4805	4925	5050	5280	5525		
25 mph			2490	2845	3220	3595	3970	4345	4575	4685	4805	5025	5260		
30 mph			2270	2735	3095	3450	3805	4165	4385	4495	4610	4830	5050		
40 mph			2270	2600	2945	3285	3625	3970	4180	4290	4385	4595	4805		
25 mph Dual	1810	2005	2195	2555	2930	3295	3560	3825	4025	4125	4235	4430	4630	4915	5015

Rim Size (inch)		Description										MSPN (CAI)			
28		440/65 R28 131D TL										96372 (386212)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
17.2	50.8	22.8	150.9	DW14L	DW15L, W13, W14L, W15L						22.8	52.3	54		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	3000	3265	3525	3955	4375	4805	5205	5600	5995	6195	6395				
20 mph	2335	2545	2755	3230	3715	4190	4565	4940							
25 mph			2625	3075	3540	3990	4355	4720							
30 mph			2515	2945	3385	3815	4165	4520							
40 mph			2405	2810	3230	3640	3970	4300							
25 mph Dual	1960	2140	2305	2710	3110	3515	3835	4155							

Rim Size (inch)		Description										MSPN (CAI)			
28		480/65 R28 136D TL										14369 (897574)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
18.7	52.7	23.5	156.3	DW15L	DW14L, W14L, W15L						24.6	63.9	57		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	3415	3695	3970	4485	4995	5510	5985	6450	6925	7155	7385				
20 mph	2600	2890	3175	3725	4275	4830	5260	5690							
25 mph			3020	3540	4070	4585	4995	5400							
30 mph			2890	3395	3900	4410	4795	5180							
40 mph			2755	3230	3715	4190	4565	4940							
25 mph Dual	2185	2425	2655	3120	3570	4035	4400	4750							

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
28		540/65 R28 142D TL										36062 (792274)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims					Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)			
20.8	56.2	24.8	166.3	DW16L	DW18L, W16L, W18L					28.0	84	61			
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	4190	4495	4805	5410	6010	6615	7165	7715	8265	8545	8820				
20 mph	3175	3495	3815	4440	5060	5690	6205	6725							
25 mph			3615	4210	4805	5400	5895	6395							
30 mph			3485	4045	4620	5180	5655	6130							
40 mph			3305	3845	4400	4940	5390	5840							
25 mph Dual	2655	2920	3185	3705	4235	4750	5190	5620							

Rim Size (inch)		Description										MSPN (CAI)			
30		540/65 R30 143D TL										28553 (223153)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims					Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)			
20.7	58	25.5	171.4	DW16L	DW18L, W16L, W18L					28.0	88	61			
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	4300	4620	4940	5555	6160	6780	7365	7935	8520	8805	9095				
20 mph	3265	3595	3925	4565	5205	5840	6370	6900							
25 mph			3750	4355	4950	5555	6065	6570							
30 mph			3595	4180	4750	5335	5820	6305							
40 mph			3415	3970	4520	5070	5545	6010							
25 mph Dual	2735	3020	3295	3825	4365	4895	5335	5775							

Rim Size (inch)		Description										MSPN (CAI)			
34		540/65 R34 145D TL										22243 (712064)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims					Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)			
20.9	62	27.3	183.3	DW16L	DW18L, W16L, W18L					28.0	96.2	61			
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	4540	4870	5205	5855	6515	7165	7780	8410	9030	9335	9645				
20 mph	3440	3815	4190	4905	5635	6350	6855	7365							
25 mph			3990	4675	5355	6040	6525	7010							
30 mph			3815	4475	5135	5800	6260	6725							
40 mph			3640	4265	4885	5510	5950	6395							
25 mph Dual	2890	3210	3515	4110	4720	5315	5745	6175							

Rim Size (inch)		Description										MSPN (CAI)			
34		540/65 R34 152D TL										99445 (214036)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims					Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)			
20.9	62.6	27.9	185.7	DW16L	DW18L, W16L, W18L					28.0	96.2	61			
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	4540	4870	5205	5855	6515	7165	7780	8410	9030	9335	9645	10195	10750	11495	11740
20 mph	3440	3815	4190	4905	5635	6350	6855	7365	7770	7980	8180	8585	8995		
25 mph			3990	4675	5355	6040	6525	7010	7410	7595	7795	8190	8575		
30 mph			3815	4475	5135	5800	6260	6725	7100	7285	7475	7850	8225		
40 mph			3640	4265	4885	5510	5950	6395	6755	6935	7110	7475	7825		
25 mph Dual	2890	3210	3515	4110	4720	5315	5745	6175	6515	6690	6855	7200	7540		

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
34		600/65 R34 151D TL										16291 (557189)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
23.4	65.1	28.8	192.8	DW20B (A)	DW18L, W18L						29.9	122.6	68		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	5355	5765	6175	6965	7750	8545	9250	9955	10650	11000	11355				
20 mph	4055	4495	4940	5745	6560	7365	8060	8750							
25 mph			4720	5480	6250	7010	7670	8335							
30 mph			4520	5260	5985	6725	7350	7980							
40 mph			4300	4995	5700	6395	7000	7605							
25 mph Dual	3395	3780	4155	4830	5500	6175	6755	7330							

Rim Size (inch)		Description										MSPN (CAI)			
38		540/65 R38 147D TL										28857 (114518)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
20.8	65.9	29.3	195.5	DW16L	DW18L, W16L, W18L						28.0	104.1	61		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	4805	5160	5510	6205	6910	7605	8255	8905	9545	9875	10195				
20 mph	3680	4055	4430	5125	5830	6525	7165	7805							
25 mph			4235	4895	5555	6215	6825	7430							
30 mph			4055	4685	5325	5950	6535	7120							
40 mph			3860	4465	5070	5675	6230	6780							
25 mph Dual	3085	3405	3725	4310	4885	5465	6010	6535							

Rim Size (inch)		Description										MSPN (CAI)			
38		600/65 R38 153D TL										29767 (228045)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
23.4	69.6	30.7	205.9	DW20B (A)	DW18L, W18L						29.9	132.1	67		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	5675	6120	6550	7395	8245	9095	9820	10560	11290	11650	12015				
20 mph	4320	4775	5225	6085	6945	7805	8530	9260							
25 mph			4980	5800	6615	7430	8125	8820							
30 mph			4760	5545	6340	7120	7780	8445							
40 mph			4540	5290	6030	6780	7420	8045							
25 mph Dual	3625	4010	4385	5105	5820	6535	7155	7760							

Rim Size (inch)		Description										MSPN (CAI)			
38		650/65 R38 157D TL										12871 (292904)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
25.4	71.6	31.5	211.8	DW20B (A)							32.5	159	71		
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	6395	6890	7385	8320	9260	10195	11035	11885	12720	13140	13560				
20 mph	4830	5335	5840	6810	7780	8750	9600	10450							
25 mph			5555	6480	7410	8335	9150	9965							
30 mph			5335	6215	7100	7980	8765	9545							
40 mph			5070	5920	6755	7605	8355	9095							
25 mph Dual	4045	4475	4895	5710	6515	7330	8060	8775							

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

Rim Size (inch)		Description										MSPN (CAI)			
42		650/65 R42 158D TL										38881 (167733)			
Section Width	Overall Diam. (in.)	Loaded Radius (in.)	Rolling Circum. (in.)	Recommended Rim	Acceptable Rims						Min. Dual / Triple Spacing (in.)	75% internal volume (gal.)	Tread depth (32nd in.)		
25.1	76	33.8	225.3	DW20B (A)								32.5	170.9	72	
Psi	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
6 mph **	6615	7110	7605	8565	9515	10470	11365	12270	13160	13605	14055				
20 mph	5070	5610	6150	7185	8225	9260	10020	10780							
25 mph			5865	6845	7835	8820	9535	10250							
30 mph			5620	6560	7505	8445	9140	9835							
40 mph			5355	6250	7155	8045	8710	9370							
25 mph Dual	4255	4705	5160	6030	6890	7760	8390	9015							

***IMPORTANT:**

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (June 2018). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque use the 20 mph line.
- When using single tire configuration:
 - add 6 psi for use on slopes of more than 20%
 - add 6 psi for intense road use exceeding 50%
- **6 mph LT (Low Torque) (max speed 6 mph).