

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
			12	80	P145/80R12	705	739	
13	80	P155/80R13	838	882	926	959		79
		P165/80R13	926	981	1025	1069		83
		P175/80R13	1025	1080	1135	1179		86
		P185/80R13	1124	1190	1246	1301		90
	70	P155/70R13	728	772	805	853		75
		P165/70R13	816	860	904	937		78
		P175/70R13	893	948	992	1036		82
		P185/70R13	992	1036	1091	1135		85
		P195/70R13	1080	1135	1190	1246		88
	60	P205/70R13	1179	1235	1301	1356		91
		P205/60R13	1014	1069	1124	1179		86
	50	P175/50R13	672	705	739	783		72
		P215/50R13	948	992	1047	1091		84
14	75	P175/75R14	1014	1069	1124	1168		86
		P185/75R14	1113	1168	1235	1290		89
		P195/75R14	1213	1279	1345	1400		92
		P205/75R14	1323	1400	1466	1532		95
		P215/75R14	1433	1521	1587	1664		98
		P225/75R14	1554	1642	1720	1797		101
	70	P175/70R14	948	1003	1047	1102		84
		P185/70R14	1036	1091	1146	1201		87
		P195/70R14	1135	1201	1257	1312		90
		P205/70R14	1235	1301	1367	1433		93
		P215/70R14	1345	1411	1488	1554		96
		P225/70R14	1455	1532	1609	1675		98
	65	P175/65R14	882	937	981	1019		81
		P185/65R14	970	1025	1069	1124		85
		P195/65R14	1058	1113	1168	1235		88
	60	P185/60R14	904	948	1003	1047		82
		P195/60R14	981	1036	1091	1135		85
		P205/60R14	1069	1135	1190	1235		88
		P215/60R14	1168	1224	1290	1345		91
		P225/60R14	1257	1323	1389	1455		94
		P235/60R14	1356	1422	1499	1565		96
P245/60R14		1455	1532	1609	1675		98	
50	P245/50R14	1246	1312	1378	1433		93	
	P265/50R14	1422	1499	1565	1642		98	
45		P225/45R14	838	882	926	963		79

* Some sizes, 45 series and lower, may be designated with LL.
The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
			14	45	P225/45R14	970	1038	
15	75	P195/75R15	1279	1345	1411	1477		94
		P205/75R15	1389	1466	1532	1598		97
		P215/75R15	1510	1587	1664	1742		100
		P225/75R15	1631	1720	1797	1874		102
		P235/75R15	1753	1852	1940	2028		105
		P265/75R15	2160	2282	2392	2469		112
	70	P205/70R15	1301	1367	1433	1499		95
		P215/70R15	1411	1488	1554	1620		97
		P225/70R15	1521	1598	1675	1753		100
		P235/70R15	1642	1731	1808	1896		102
		P245/70R15	1764	1852	1951	2028		105
		P255/70R15	1885	1984	2083	2183		108
		P265/70R15	2017	2127	2227	2337		110
		P285/70R15	2293	2414	2535	2679		115
	65	P175/65R15	849	926	992	1069	1102	84
		P185/65R15	1014	1069	1124	1168		86
		P195/65R15	1113	1168	1235	1279		89
		P205/65R15	1213	1279	1334	1400		92
		P215/65R15	1312	1378	1455	1510		95
		P235/65R15	1521	1609	1687	1764		100
		P255/65R15	1753	1852	1940	2028		105
		P295/65R15	2271	2392	2502	2601		114
	60	P185/60R15	948	1003	1047	1102		84
		P195/60R15	1036	1091	1146	1190		87
		P205/60R15	1124	1190	1246	1301		90
		P215/60R15	1224	1290	1345	1411		93
		P225/60R15	1312	1389	1455	1521		95
		P235/60R15	1422	1499	1565	1642		98
		P245/60R15	1521	1609	1687	1753		100
		P255/60R15	1631	1720	1808	1885		102
P275/60R15		1863	1962	2050	2149		107	
P295/60R15		2105	2216	2326	2403		111	
P315/60R15	2359	2480	2601	2756		116		
55	P195/55R15	959	1014	1058	1102		84	
	P205/55R15	1047	1102	1157	1201		87	
	P225/55R15	1224	1290	1345	1389		92	
	P255/55R15	1510	1587	1664	1742		100	
	P345/55R15	2557	2701	2833	2910		118	

* Some sizes, 45 series and lower, may be designated with LL.

The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	*36		
15	50	P195/50R15	893	937	981	1019		81	
		P205/50R15	970	1014	1069	1113		84	
		P215/50R15	1047	1102	1157	1201		87	
		P225/50R15	1124	1190	1246	1301		90	
		P245/50R15	1301	1367	1444	1499		95	
		P265/50R15	1488	1565	1642	1720		99	
		P275/50R15	1587	1675	1753	1830		101	
		P295/50R15	1786	1885	1973	2061		105	
		P305/50R15	1896	1995	2094	2194		108	
		P325/50R15	2116	2238	2337	2447		112	
16	75	P215/75R16	1576	1653	1742	1819		101	
		P225/75R16	1698	1786	1874	1984		104	
		P235/75R16	1830	1929	2028	2094		106	
		P245/75R16	1962	2072	2172	2271		109	
		P265/75R16	2249	2370	2491	2601		114	
	70	P205/70R16	1356	1433	1499	1565		96	
		P215/70R16	1466	1554	1620	1709		99	
		P225/70R16	1587	1675	1753	1819		101	
		P235/70R16	1709	1808	1885	1984		104	
		P245/70R16	1841	1940	2028	2094		106	
		P255/70R16	1962	2072	2172	2271		109	
		P265/70R16	2105	2216	2326	2403		111	
			P275/70R16	2238	2359	2480	2601		114
	65	P205/65R16	1268	1334	1400	1477		94	
		P215/65R16	1367	1444	1521	1565		96	
		P225/65R16	1477	1565	1642	1709		99	
		P235/65R16	1598	1675	1764	1819		101	
		P255/65R16	1830	1929	2028	2094		106	
P265/65R16		1962	2061	2160	2271		109		
P275/65R16		2083	2205	2304	2403		111		
P285/65R16		2216	2337	2458	2535		113		
P295/65R16		2359	2491	2612	2756		116		
			P185/60R16	904	981	1058	1135	1168	86
60	P195/60R16	981	1069	1157	1235	1279		89	
	P205/60R16	1179	1246	1301	1356		91		
	P215/60R16	1279	1345	1411	1477		94		
	P225/60R16	1378	1455	1521	1609		97		
	P235/60R16	1477	1565	1642	1709		99		
	P255/60R16	1698	1797	1885	1984		104		

* Some sizes, 45 series and lower, may be designated with LL.
The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
			16	60	P265/60R16	1819	1918	
		P285/60R16	2061	2172	2282	2403		111
	55	P195/55R16	1003	1058	1113	1168		86
		P205/55R16	1091	1157	1213	1279		89
		P215/55R16	1179	1246	1312	1356		91
		P225/55R16	1279	1345	1411	1477		94
		P235/55R16	1378	1444	1521	1565		96
	50	P195/50R16	937	981	1036	1074		83
		P205/50R16	1014	1069	1124	1168		86
		P215/50R16	1091	1157	1213	1279		89
		P225/50R16	1179	1246	1301	1367		91
		P235/50R16	1268	1334	1400	1477		94
		P245/50R16	1356	1433	1510	1576		96
		P255/50R16	1455	1532	1609	1687		99
		P265/50R16	1554	1642	1720	1797		101
		P275/50R16	1653	1742	1830	1929		103
		P295/50R16	1863	1962	2061	2149		107
	45	P205/45R16	794	838	882	908		77
		P205/45R16	827	893	970	1036	1074	83
		P245/45R16	1069	1124	1179	1235		88
		P245/45R16	1226	1312	1396	1477		94
		P265/45R16	1213	1279	1345	1389		92
	40	P205/40R16	728	772	805	853		75
		P205/40R16	798	855	910	963		79
17	75	P235/75R17	1907	2017	2105	2205		108
		P245/75R17	2050	2160	2271	2337		110
		P255/75R17	2194	2315	2425	2535		113
	70	P215/70R17	1422	1521	1620	1720	1764	100
		P235/70R17	1786	1885	1973	2039		105
		P245/70R17	1918	2017	2116	2205		108
		P255/70R17	2050	2160	2271	2337		110
		P265/70R17	2194	2315	2425	2535		113
		P285/70R17	2480	2623	2745	2833		117
	65	P215/65R17	1433	1510	1587	1653		98
		P225/65R17	1543	1631	1709	1764		100
		P235/65R17	1664	1753	1841	1929		103
		P245/65R17	1786	1885	1973	2039		105
		P255/65R17	1907	2017	2116	2205		108
		P265/65R17	2039	2149	2260	2337		110

* Some sizes, 45 series and lower, may be designated with LL.

The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
17	65	P275/65R17	2172	2293	2403	2535		113
		P285/65R17	2315	2436	2557	2679		115
	60	P215/60R17	1334	1411	1477	1521		95
		P225/60R17	1444	1521	1587	1653		98
		P235/60R17	1543	1631	1709	1764		100
		P255/60R17	1775	1874	1962	2039		105
		P265/60R17	1896	1995	2094	2205		108
		P275/60R17	2017	2127	2238	2337		110
	55	P215/55R17	1235	1301	1367	1433		93
		P225/55R17	1334	1411	1477	1521		95
		P235/55R17	1433	1510	1587	1653		98
		P255/55R17	1642	1731	1819	1874		102
		P265/55R17	1753	1852	1940	2039		105
		P275/55R17	1874	1973	2072	2149		107
	50	P205/50R17	1058	1113	1168	1235		88
		P215/50R17	1146	1213	1268	1323		90
		P225/50R17	1235	1301	1367	1433		93
		P235/50R17	1323	1400	1466	1521		95
		P245/50R17	1422	1499	1576	1653		98
		P255/50R17	1521	1598	1687	1764		100
	45	P215/45R17	996	1067	1135	1201		87
		P225/45R17	970	1025	1069	1102		84
		P225/45R17	1098	1175	1250	1323		90
		P235/45R17	1036	1091	1146	1201		87
		P235/45R17	1188	1272	1354	1433		93
		P245/45R17	1113	1179	1235	1279		89
		P245/45R17	1261	1351	1437	1521		95
		P255/45R17	1190	1257	1312	1389		92
		P255/45R17	1371	1468	1563	1653		98
		P305/45R17	1609	1698	1775	1874		102
		P305/45R17	1883	2017	2145	2271		109
	P315/45R17	1698	1797	1885	1984		104	
	40	P205/40R17	761	805	849	882		76
		P205/40R17	822	882	937	992		80
		P215/40R17	827	871	915	963		79
		P235/40R17	959	1003	1058	1102		84
P245/40R17		1025	1080	1135	1168		86	
P255/40R17		1091	1146	1213	1279		89	
P255/40R17		1226	1312	1396	1477		94	

* Some sizes, 45 series and lower, may be designated with LL.
The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	*36		
17	40	P265/40R17	1168	1224	1290	1356		91	
		P275/40R17	1235	1301	1367	1433		93	
		P275/40R17	1371	1468	1563	1653		98	
		P285/40R17	1312	1389	1455	1521		95	
		P285/40R17	1464	1567	1667	1764		100	
	35	P285/35R17	1058	1113	1168	1235		88	
		P315/35R17	1246	1323	1378	1433		93	
		P315/35R17	1554	1664	1770	1874		102	
	18	70	P335/35R17	1389	1466	1532	1609		97
			P255/70R18	2127	2249	2359	2469		112
			P265/70R18	2271	2403	2513	2601		114
		65	P275/70R18	2227	2381	2535	2679	2756	116
P235/65R18			1731	1830	1918	1984		104	
P255/65R18			1984	2094	2194	2271		109	
P265/65R18			2116	2238	2348	2469		112	
P275/65R18			2260	2381	2502	2601		114	
P225/60R18			1499	1576	1653	1709		99	
60		P235/60R18	1609	1698	1786	1874		102	
		P245/60R18	1731	1819	1907	1984		104	
		P255/60R18	1852	1951	2039	2149		107	
		P265/60R18	1973	2083	2183	2271		109	
		P275/60R18	2094	2216	2326	2403		111	
		P285/60R18	2227	2348	2469	2601		114	
55		P215/55R18	1290	1367	1433	1477		94	
		P225/55R18	1389	1466	1543	1609		97	
		P235/55R18	1499	1576	1653	1709		99	
	P245/55R18	1598	1687	1775	1874		102		
	P255/55R18	1709	1808	1896	1984		104		
	P265/55R18	1830	1929	2017	2094		106		
	P275/55R18	1951	2050	2149	2271		109		
	P285/55R18	2072	2183	2282	2403		111		
50	P215/50R18	1069	1157	1257	1345	1389	92		
	P225/50R18	1290	1356	1422	1477		94		
	P235/50R18	1389	1455	1532	1609		97		
	P245/50R18	1488	1565	1642	1709		99		
	P255/50R18	1587	1675	1753	1819		101		
45	P215/45R18	1060	1135	1208	1279		89		
	P225/45R18	1124	1204	1281	1356		91		
	P235/45R18	1080	1146	1201	1235		88		

* Some sizes, 45 series and lower, may be designated with LL.

The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
18	45	P235/45R18	1226	1312	1396	1477		94
		P245/45R18	1299	1391	1479	1565		96
		P255/45R18	1246	1312	1367	1433		93
		P255/45R18	1418	1517	1614	1709		99
		P265/45R18	1466	1576	1675	1775	1819	101
		P295/45R18	1587	1664	1753	1819		101
		P295/45R18	1828	1958	2083	2205		108
	40	P215/40R18	860	904	959	992		80
		P225/40R18	926	981	1025	1074		83
		P225/40R18	1023	1096	1166	1235		88
		P235/40R18	992	1047	1102	1135		85
		P245/40R18	1069	1124	1179	1235		88
		P245/40R18	1188	1272	1354	1433		93
		P255/40R18	1135	1201	1257	1323		90
		P265/40R18	1213	1279	1345	1389		92
		P275/40R18	1290	1356	1422	1477		94
		P285/40R18	1367	1444	1510	1565		96
	P315/40R18	1620	1709	1786	1874		102	
	35	P215/35R18	694	739	772	805		73
		P245/35R18	860	904	948	992		80
		P255/35R18	915	970	1014	1047		82
		P265/35R18	981	1025	1080	1135		85
		P275/35R18	1036	1091	1146	1201		87
		P285/35R18	1102	1157	1224	1279		89
		P295/35R18	1168	1235	1290	1356		91
	30	P285/30R18	948	1014	1080	1135	1168	86
		P315/30R18	1179	1246	1312	1356		91
		P335/30R18	1312	1378	1444	1521		95
		P345/30R18	1378	1455	1521	1609		97
	19	60	P255/60R19	1918	2028	2127	2205	
55		P235/55R19	1554	1642	1720	1819		101
		P245/55R19	1554	1664	1775	1874	1929	103
50		P235/50R19	1312	1433	1543	1653	1709	99
		P255/50R19	1554	1664	1775	1874	1929	103
45		P225/45R19	1069	1157	1257	1345	1389	92
		P235/45R19	1261	1351	1437	1521		95
		P245/45R19	1268	1378	1488	1598	1653	98
		P255/45R19	1290	1367	1433	1477		94
		P255/45R19	1464	1567	1667	1764		100

* Some sizes, 45 series and lower, may be designated with LL.
The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	*36		
19	40	P245/40R19	1135	1235	1334	1433	1477	94	
		P255/40R19	1190	1257	1312	1356		91	
		P255/40R19	1299	1391	1479	1565		96	
		P265/40R19	1268	1378	1488	1598	1653	98	
		P275/40R19	1345	1411	1488	1565		96	
		P275/40R19	1508	1616	1720	1819		101	
		P315/40R19	1687	1775	1863	1929		103	
		P315/40R19	1883	2017	2145	2271		109	
	35	P215/35R19	728	772	805	853		75	
		P245/35R19	1060	1135	1208	1279		89	
		P285/35R19	1146	1213	1268	1323		90	
		30	P285/30R19	970	1036	1102	1168	1201	87
			P285/30R19	1135	1235	1334	1433	1477	94
			P325/30R19	1301	1367	1433	1477		94
	P345/30R19		1433	1510	1587	1653		98	
	P355/30R19	1378	1477	1576	1664	1709	99		
	25	P295/25R19	1014	1102	1190	1279	1323	90	
	20	60	P245/60R20	1742	1863	1973	2094	2149	107
			P275/60R20	2260	2381	2502	2601		114
55		P235/55R20	1510	1620	1720	1830	1874	102	
		P255/55R20	1742	1863	1973	2094	2149	107	
		P275/55R20	2094	2216	2315	2403		111	
50		P245/50R20	1510	1620	1720	1830	1874	102	
		P255/50R20	1709	1808	1896	1984		104	
		P265/50R20	1830	1929	2017	2094		106	
		P285/50R20	2061	2172	2271	2403		111	
45		P235/45R20	1299	1391	1479	1565		96	
		P255/45R20	1466	1576	1675	1775	1819	101	
		P275/45R20	1737	1861	1980	2094		106	
40		P245/40R20	1157	1224	1279	1323		90	
		P295/40R20	1565	1653	1731	1819		101	
		P295/40R20	1737	1861	1980	2094		106	
35		P255/35R20	1188	1272	1354	1433		93	
		P275/35R20	1124	1190	1246	1279		89	
		P285/35R20	1124	1201	1279	1356	1389	92	
25		P335/25R20	1190	1279	1356	1433	1477	94	
21	45	P255/45R21	1554	1664	1770	1874		102	
		P265/45R21	1598	1720	1830	1929	1984	104	
22	50	P275/50R22	1940	2083	2216	2337	2403	111	

* Some sizes, 45 series and lower, may be designated with LL.

The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	*36	
			22	45	P275/45R22	1828	1958	
		P285/45R22	1938	2077	2209	2337	110	

* Some sizes, 45 series and lower, may be designated with LL.
The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

P Metric Extra Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)			LOAD INDEX
			38	41	*42	
			13	50	P175/50R13	
14	75	P195/75R14	1466	1521		95
		P205/75R14	1587	1653		98
14	65	P175/65R14	1058	1102		84
		P195/65R14	1279	1323		90
15	75	P205/75R15	1664	1709		99
		P215/75R15	1808	1874		102
		P225/75R15	1951	2028		105
		P235/75R15	2105	2183		108
	70	P245/70R15	2116	2194		108
		P255/70R15	2271	2337		110
	65	P205/65R15	1455	1521		95
		P255/60R15	1962	2039		105
	50	P245/50R15	1565	1609		97
		P305/50R15	2282	2337		110
16	75	P225/75R16	2039	2094		106
		P235/75R16	2205	2271		109
	70	P235/70R16	2050	2149		107
		P255/70R16	2359	2469		112
	60	P205/60R16	1422	1477		94
	50	P205/50R16	1213	1279		89
	40	P205/40R16	1023	1074		83
	17	70	P235/70R17	2149	2205	
60		P235/60R17	1863	1929		103
50		P205/50R17	1279	1323		90
		P215/50R17	1378	1433		93
18	50	P215/50R18	1433	1521	1565	96
		P235/50R18	1664	1709		99
19	50	P245/50R19	1819	1929	1984	104
20	45	P295/45R20	2480	2601		114
22	45	P275/45R22	2352	2469		112
		P305/45R22	2773	2910		118
23	40	P265/40R22	1896	1995	2039	105
	40	P305/40R23	2553	2679		115

The (lbs.) figures tabulated above are converted from the calculated "kg" values then rounded to the nearest pound.

- Minimum cold inflation pressures shall be as indicated in the table for corresponding tire loads.
- If the vehicle is equipped with a Tire Pressure Monitoring System (TPMS), the load on the tire must not exceed the tire load capacity based on the inflation pressure at the point of illumination of the TPMS telltale.
- Cold inflation pressures may be increased above those applicable to the tire loads up to the maximum marked on the tire with no increase in load. For tires used in the United States, the "Maximum Permissible Inflation Pressure" which must be marked on the tire as prescribed by Federal Motor Vehicle Safety Standard No. 109 and 139 shall be one of the following:

P TYPE TIRE LOAD VERSION	MAX. PERMISSIBLE INFLATION PRESSURE MARKING	CORRESPONDING MAXIMUM LOAD
STANDARD LOAD, LL, SL (ISO)	240 kPa (35 psi)	240 kPa (35 psi) Load
	300 kPa (44 psi)	240 kPa (35 psi) Load, *250 kPa (36 psi) Load
	350 kPa (51 psi)	240 kPa (35 psi) Load, *250 kPa (36 psi) Load
EXTRA LOAD (XL), XL (ISO)	280 kPa (41 psi)	280 kPa (41 psi) Load
	340 kPa (50 psi)	280 kPa (41 psi) Load, *290 kPa (42 psi) Load

- *Tire sizes with 250 kPa (36 psi) and 290 kPa (42 psi) reference pressures have internationally harmonized load ratings.

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	250 *kPa		
14	75	205/75R14	1166	1272	1376	1479	1521	95	
	70	175/70R14	845	922	997	1072	1102	84	
		185/70R14	946	1033	1117	1200	1235	88	
		195/70R14	1039	1134	1227	1318	1356	91	
		205/70R14	1166	1272	1376	1479	1521	95	
	65	165/65R14	738	806	872	937	963	79	
		175/65R14	803	876	948	1018	1047	82	
		185/65R14	895	977	1057	1136	1168	86	
	60	195/65R14	980	1069	1157	1243	1279	89	
		185/60R14	803	876	948	1018	1047	82	
		195/60R14	895	977	1057	1136	1168	86	
		205/60R14	946	1033	1117	1200	1235	88	
	15	75	215/60R14	1039	1134	1227	1318	1356	91
			235/75R15	1563	1706	1845	1982	2039	105
		70	255/75R15	1791	1954	2115	2272	2337	110
			195/70R15	1064	1162	1257	1350	1389	92
205/70R15			1200	1309	1416	1522	1565	96	
215/70R15			1267	1383	1496	1607	1653	98	
225/70R15			1352	1475	1596	1715	1764	100	
235/70R15			1478	1613	1746	1875	1929	103	
65		265/70R15	1892	2065	2234	2400	2469	112	
		175/65R15	845	922	997	1072	1102	84	
		185/65R15	946	1033	1117	1200	1235	88	
		195/65R15	1039	1134	1227	1318	1356	91	
		205/65R15	1132	1235	1337	1436	1477	94	
60		215/65R15	1200	1309	1416	1522	1565	96	
		185/60R15	845	922	997	1072	1102	84	
		195/60R15	946	1033	1117	1200	1235	88	
	205/60R15	1039	1134	1227	1318	1356	91		
	215/60R15	1132	1235	1337	1436	1477	94		
	225/60R15	1200	1309	1416	1522	1565	96		
55	235/60R15	1267	1383	1496	1607	1653	98		
	185/55R15	803	876	948	1018	1047	82		
	195/55R15	870	950	1027	1104	1135	85		
	205/55R15	946	1033	1117	1200	1235	88		
50	225/55R15	1064	1162	1257	1350	1389	92		
	195/50R15	803	876	948	1018	1047	82		
	205/50R15	895	977	1057	1136	1168	86		
		215/50R15	946	1033	1117	1200	1235	88	

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
 *Conversion 100 kPa = 14.5 psi

Section 10
Load & Inflation

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	250 *kPa	
15	50	225/50R15	1039	1134	1227	1318	1356	91
	45	195/45R15	718	784	848	911	937	78
		225/45R15	921	1005	1087	1168	1202	87
40	245/40R15	946	1033	1117	1200	1235	88	
16	75	225/75R16	1521	1659	1795	1929	1984	104
		245/75R16	1842	2010	2174	2336	2403	111
	70	215/70R16	1352	1475	1596	1715	1764	100
		225/70R16	1478	1613	1746	1875	1929	103
		235/70R16	1605	1752	1895	2036	2094	106
		245/70R16	1647	1798	1945	2090	2150	107
		255/70R16	1842	2010	2174	2336	2403	111
		265/70R16	1892	2065	2234	2400	2469	112
		275/70R16	1994	2176	2354	2529	2601	114
	65	185/65R16	980	1069	1157	1243	1279	89
		205/65R16	1166	1272	1376	1479	1521	95
		215/65R16	1267	1383	1496	1607	1653	98
		225/65R16	1352	1475	1596	1715	1764	100
		235/65R16	1478	1613	1746	1875	1929	103
		255/65R16	1740	1899	2055	2207	2271	109
	60	175/60R16	803	876	948	1018	1047	82
		195/60R16	980	1069	1157	1243	1279	89
		205/60R16	1064	1162	1257	1350	1389	92
		215/60R16	1166	1272	1376	1479	1521	95
		225/60R16	1267	1383	1496	1607	1653	98
		235/60R16	1352	1475	1596	1715	1764	100
	55	195/55R16	921	1005	1087	1168	1202	87
		205/55R16	1039	1134	1227	1318	1356	91
		215/55R16	1098	1198	1297	1393	1433	93
		225/55R16	1166	1272	1376	1479	1521	95
	50	195/50R16	845	922	997	1072	1102	84
		205/50R16	921	1005	1087	1168	1202	87
215/50R16		1014	1106	1197	1286	1323	90	
225/50R16		1064	1162	1257	1350	1389	92	
235/50R16		1166	1272	1376	1479	1521	95	
245/50R16		1233	1346	1456	1564	1609	97	
255/50R16		1309	1429	1546	1661	1709	99	
45	195/45R16	760	830	898	964	992	80	
	205/45R16	823	898	972	1044	1074	83	
	215/45R16	895	977	1057	1136	1168	86	

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	250 *kPa		
			16	45	225/45R16	980	1069		1157
		245/45R16	1132	1235	1337	1436	1477	94	
17	70	245/70R17	1791	1954	2115	2272	2337	2337	110
		255/70R17	1892	2065	2234	2400	2469	2469	112
		265/70R17	2053	2240	2424	2604	2679	2679	115
	65	215/65R17	1309	1429	1546	1661	1709	1709	99
		225/65R17	1436	1567	1696	1822	1874	1874	102
		235/65R17	1521	1659	1795	1929	1984	1984	104
		245/65R17	1647	1798	1945	2090	2150	2150	107
		255/65R17	1791	1954	2115	2272	2337	2337	110
		265/65R17	1892	2065	2234	2400	2469	2469	112
		275/65R17	2053	2240	2424	2604	2679	2679	115
	60	215/60R17	1200	1309	1416	1522	1565	1565	96
		225/60R17	1309	1429	1546	1661	1709	1709	99
		235/60R17	1436	1567	1696	1822	1874	1874	102
		255/60R17	1605	1752	1895	2036	2094	2094	106
	55	195/55R17	946	1033	1117	1200	1235	1235	88
		205/55R17	1039	1134	1227	1318	1356	1356	91
		215/55R17	1132	1235	1337	1436	1477	1477	94
		225/55R17	1233	1346	1456	1564	1609	1609	97
		235/55R17	1309	1429	1546	1661	1709	1709	99
		245/55R17	1436	1567	1696	1822	1874	1874	102
		255/55R17	1521	1659	1795	1929	1984	1984	104
	50	275/55R17	1740	1899	2055	2207	2271	2271	109
		205/50R17	980	1069	1157	1243	1279	1279	89
		215/50R17	1039	1134	1227	1318	1356	1356	91
		225/50R17	1132	1235	1337	1436	1477	1477	94
		235/50R17	1200	1309	1416	1522	1565	1565	96
		245/50R17	1309	1429	1546	1661	1709	1709	99
		255/50R17	1394	1521	1646	1768	1819	1819	101
	45	205/45R17	845	922	997	1072	1102	1102	84
		215/45R17	921	1005	1087	1168	1202	1202	87
		225/45R17	1039	1134	1227	1318	1356	1356	91
		235/45R17	1132	1235	1337	1436	1477	1477	94
245/45R17		1166	1272	1376	1479	1521	1521	95	
255/45R17		1267	1383	1496	1607	1653	1653	98	
40	205/40R17	760	830	898	964	992	992	80	
	215/40R17	823	898	972	1044	1074	1074	83	
	235/40R17	1014	1106	1197	1286	1323	1323	90	

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
 *Conversion 100 kPa = 14.5 psi

Section 10
Load & Inflation

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	250 *kPa	
			17	40	245/40R17	1039	1134	
		255/40R17	1132	1235	1337	1436	1477	94
		265/40R17	1200	1309	1416	1522	1565	96
		275/40R17	1267	1383	1496	1607	1653	98
		285/40R17	1352	1475	1596	1715	1764	100
	35	225/35R17	803	876	948	1018	1047	82
		265/35R17	1064	1162	1257	1350	1389	92
		315/35R17	1436	1567	1696	1822	1874	102
		335/35R17	1605	1752	1895	2036	2094	106
	70	255/70R18	1943	2120	2294	2465	2535	113
	65	235/65R18	1605	1752	1895	2036	2094	106
		255/65R18	1842	2010	2174	2336	2403	111
		265/65R18	1994	2176	2354	2529	2601	114
	60	225/60R18	1352	1475	1596	1715	1764	100
		235/60R18	1478	1613	1746	1875	1929	103
		245/60R18	1563	1706	1845	1982	2039	105
		265/60R18	1791	1954	2115	2272	2337	110
		275/60R18	1943	2120	2294	2465	2535	113
		285/60R18	2112	2305	2494	2679	2756	116
	55	215/55R18	1166	1272	1376	1479	1521	95
		225/55R18	1267	1383	1496	1607	1653	98
		235/55R18	1352	1475	1596	1715	1764	100
		245/55R18	1478	1613	1746	1875	1929	103
		255/55R18	1563	1706	1845	1982	2039	105
	50	225/50R18	1166	1272	1376	1479	1521	95
		235/50R18	1233	1346	1456	1564	1609	97
		245/50R18	1352	1475	1596	1715	1764	100
		285/50R18	1740	1899	2055	2207	2271	109
	45	215/45R18	980	1069	1157	1243	1279	89
		225/45R18	1039	1134	1227	1318	1356	91
		235/45R18	1132	1235	1337	1436	1477	94
		245/45R18	1200	1309	1416	1522	1565	96
		255/45R18	1309	1429	1546	1661	1709	99
		265/45R18	1465	1573	1677	1777	1819	101
		275/45R18	1478	1613	1746	1875	1929	103
		295/45R18	1690	1844	1995	2143	2205	108
	40	215/40R18	870	950	1027	1104	1135	85
		225/40R18	946	1033	1117	1200	1235	88
		235/40R18	1039	1134	1227	1318	1356	91

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX	
			26	29	32	35	250 *kPa		
18	40	245/40R18	1098	1198	1297	1393	1433	93	
		255/40R18	1166	1272	1376	1479	1521	95	
		265/40R18	1233	1346	1456	1564	1609	97	
		275/40R18	1309	1429	1546	1661	1709	99	
		285/40R18	1394	1521	1646	1768	1819	101	
	35	215/35R18	760	830	898	964	992	80	
		235/35R18	895	977	1057	1136	1168	86	
		245/35R18	946	1033	1117	1200	1235	88	
		255/35R18	1014	1106	1197	1286	1323	90	
		265/35R18	1098	1198	1297	1393	1433	93	
		275/35R18	1166	1272	1376	1479	1521	95	
		285/35R18	1233	1346	1456	1564	1609	97	
		295/35R18	1309	1429	1546	1661	1709	99	
	30	345/35R18	1740	1899	2055	2207	2271	109	
		285/30R18	1098	1198	1297	1393	1433	93	
		295/30R18	1132	1235	1337	1436	1477	94	
		315/30R18	1267	1383	1496	1607	1653	98	
	19	70	335/30R18	1436	1567	1696	1822	1874	102
			285/70R19	845	922	997	1072	1102	84
		60	175/60R19	895	977	1057	1136	1168	86
255/60R19			1740	1899	2055	2207	2271	109	
55		235/55R19	1394	1521	1646	1768	1819	101	
		245/55R19	1554	1668	1779	1885	1929	103	
		265/55R19	1740	1899	2055	2207	2271	109	
		275/55R19	1842	2010	2174	2336	2403	111	
50		235/50R19	1309	1429	1546	1661	1709	99	
		245/50R19	1394	1521	1646	1768	1819	101	
		255/50R19	1478	1613	1746	1875	1929	103	
45		245/45R19	1267	1383	1496	1607	1653	98	
		255/45R19	1352	1475	1596	1715	1764	100	
		265/45R19	1510	1621	1728	1831	1874	102	
		285/45R19	1647	1798	1945	2090	2150	107	
40		225/40R19	980	1069	1157	1243	1279	89	
	235/40R19	1064	1162	1257	1350	1389	92		
	245/40R19	1132	1235	1337	1436	1477	94		
	255/40R19	1200	1309	1416	1522	1565	96		
	265/40R19	1267	1383	1496	1607	1653	98		
	275/40R19	1394	1521	1646	1768	1819	101		
	285/40R19	1478	1613	1746	1875	1929	103		

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
 *Conversion 100 kPa = 14.5 psi

Section 10
Load & Inflation

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	250 *kPa	
19	35	225/35R19	845	922	997	1072	1102	84
		235/35R19	921	1005	1087	1168	1202	87
		245/35R19	980	1069	1157	1243	1279	89
		255/35R19	1064	1162	1257	1350	1389	92
		265/35R19	1132	1235	1337	1436	1477	94
		275/35R19	1200	1309	1416	1522	1565	96
		285/35R19	1309	1429	1546	1661	1709	99
	295/35R19	1352	1475	1596	1715	1764	100	
	30	265/30R19	980	1069	1157	1243	1279	89
		275/30R19	1064	1162	1257	1350	1389	92
		285/30R19	1132	1235	1337	1436	1477	94
		315/30R19	1352	1475	1596	1715	1764	100
		325/30R19	1465	1573	1677	1777	1819	101
		345/30R19	1563	1706	1845	1982	2039	105
20	60	155/60R20	760	830	898	964	992	80
		245/60R20	1742	1863	1973	2094	2149	107
	55	175/55R20	870	950	1027	1104	1135	85
		275/55R20	1943	2120	2294	2465	2535	113
	50	245/50R20	1510	1621	1728	1831	1874	102
		265/50R20	1647	1798	1945	2090	2150	107
		275/50R20	1740	1899	2055	2207	2271	109
		285/50R20	1892	2065	2234	2400	2469	112
		305/50R20	2112	2305	2494	2679	2756	116
	45	215/45R20	1039	1134	1227	1318	1356	91
		245/45R20	1309	1429	1546	1661	1709	99
		255/45R20	1394	1521	1646	1768	1819	101
	40	245/40R20	1166	1272	1376	1479	1521	95
		275/40R20	1436	1567	1696	1822	1874	102
		295/40R20	1605	1752	1895	2036	2094	106
	35	235/35R20	946	1033	1117	1200	1235	88
		245/35R20	1039	1134	1227	1318	1356	91
		255/35R20	1098	1198	1297	1393	1433	93
		265/35R20	1166	1272	1376	1479	1521	95
		275/35R20	1267	1383	1496	1607	1653	98
285/35R20		1352	1475	1596	1715	1764	100	
295/35R20		1465	1573	1677	1777	1819	101	
305/35R20		1521	1659	1795	1929	1984	104	
315/35R20		1605	1752	1895	2036	2094	106	
325/35R20	1690	1844	1995	2143	2205	108		

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Standard Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					LOAD INDEX
			26	29	32	35	250 *kPa	
			20	30	285/30R20	1166	1272	
		295/30R20	1233	1346	1456	1564	1609	97
		305/30R20	1309	1429	1546	1661	1709	99
		335/30R20	1521	1659	1795	1929	1984	104
		345/30R20	1687	1811	1931	2047	2094	106
	45	275/45R21	1732	1859	1982	2101	2150	107
	40	245/40R21	1200	1309	1416	1522	1565	96
		265/40R21	1394	1521	1931	2047	2094	101
		315/40R21	1936	2078	2216	2348	2403	111
	35	285/35R21	1394	1521	1646	1768	1819	101
		295/35R21	1478	1613	1746	1875	1929	103
	30	295/30R21	1267	1383	1496	1607	1653	98
		325/30R21	1521	1659	1795	1929	1984	104
	25	325/25R21	1267	1383	1496	1607	1653	98
	55	325/55R22	2112	2305	2494	2679	2756	116
	35	285/35R22	1436	1567	1696	1822	1874	102
		325/35R22	1883	2021	2155	2284	2337	110

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
 *Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					290 kPa*	LOAD INDEX
			26	29	32	35	38		
14	70	175/70R14	840	917	992	1066	1138	1235	88
		185/70R14	945	1032	1116	1199	1281	1389	92
	65	175/65R14	795	868	939	1009	1077	1168	86
		185/65R14	900	982	1063	1142	1220	1323	90
	60	185/60R14	795	868	939	1009	1077	1168	86
15	75	235/75R15	1545	1686	1825	1960	2094	2271	109
	65	175/65R15	840	917	992	1066	1138	1235	88
		185/65R15	945	1032	1116	1199	1281	1389	92
		195/65R15	1035	1130	1222	1313	1403	1521	95
		205/65R15	1163	1269	1373	1475	1575	1709	99
		215/65R15	1200	1310	1417	1523	1626	1764	100
	60	185/60R15	840	917	992	1066	1138	1235	88
		195/60R15	945	1032	1116	1199	1281	1389	92
		205/60R15	1035	1130	1222	1313	1403	1521	95
	55	185/55R15	795	868	939	1009	1077	1168	86
		195/55R15	870	950	1027	1104	1179	1279	89
	50	195/50R15	795	868	939	1009	1077	1168	86
		205/50R15	870	950	1027	1104	1179	1279	89
		225/50R15	1035	1130	1222	1313	1403	1521	95
	16	75	225/75R16	1500	1637	1772	1903	2033	2205
70		225/70R16	1463	1596	1727	1856	1982	2150	107
		245/70R16	1635	1785	1931	2074	2216	2403	111
65		205/65R16	1163	1269	1373	1475	1575	1709	99
		215/65R16	1275	1392	1506	1618	1728	1874	102
60		205/60R16	1065	1163	1258	1351	1443	1565	96
		215/60R16	1163	1269	1373	1475	1575	1709	99
		225/60R16	1275	1392	1506	1618	1728	1874	102
		235/60R16	1350	1474	1594	1713	1829	1984	104
55		185/55R16	818	892	965	1037	1108	1202	87
		195/55R16	923	1007	1089	1170	1250	1356	91
		205/55R16	1005	1097	1187	1275	1362	1477	94
		215/55R16	1095	1195	1293	1389	1484	1609	97
		225/55R16	1163	1269	1373	1475	1575	1709	99
50		205/50R16	923	1007	1089	1170	1250	1356	91
45		195/45R16	750	819	886	952	1016	1102	84
	205/45R16	818	892	965	1037	1108	1202	87	
	215/45R16	900	982	1063	1142	1220	1323	90	
	225/45R16	975	1064	1151	1237	1321	1433	93	
40	205/40R16	731	797	863	927	990	1074	83	

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)						LOAD INDEX
			26	29	32	35	38	290 kPa*	
			16	40	215/40R16	795	868	939	
17	65	235/65R17	1500	1637	1772	1903	2033	2205	108
	60	225/60R17	1313	1433	1550	1665	1779	1929	103
		245/60R17	1500	1637	1772	1903	2033	2205	108
	55	195/55R17	945	1032	1116	1199	1281	1389	92
		205/55R17	1035	1130	1222	1313	1403	1521	95
		215/55R17	1125	1228	1329	1427	1524	1653	98
		225/55R17	1238	1351	1462	1570	1677	1819	101
		235/55R17	1313	1433	1550	1665	1779	1929	103
		255/55R17	1500	1637	1772	1903	2033	2205	108
	50	205/50R17	975	1064	1151	1237	1321	1433	93
		215/50R17	1035	1130	1222	1313	1403	1521	95
		225/50R17	1125	1228	1329	1427	1524	1653	98
		235/50R17	1200	1310	1417	1523	1626	1764	100
	45	205/45R17	840	917	992	1066	1138	1235	88
		215/45R17	923	1007	1089	1170	1250	1356	91
		225/45R17	1005	1097	1187	1275	1362	1477	94
		235/45R17	1095	1195	1293	1389	1484	1609	97
		245/45R17	1163	1269	1373	1475	1575	1709	99
	40	205/40R17	750	819	886	952	1016	1102	84
		215/40R17	818	892	965	1037	1108	1202	87
235/40R17		1005	1097	1187	1275	1362	1477	94	
245/40R17		1035	1130	1222	1313	1403	1521	95	
255/40R17		1125	1228	1329	1427	1524	1653	98	
18	65	235/65R18	1590	1736	1878	2017	2155	2337	110
	60	225/60R18	1350	1474	1594	1713	1829	1984	104
		235/60R18	1463	1596	1727	1856	1982	2150	107
		255/60R18	1680	1834	1984	2132	2277	2469	112
		265/60R18	1770	1932	2090	2246	2398	2601	114
		285/60R18	2101	2292	2480	2664	2846	3086	120
	55	215/55R18	1163	1269	1373	1475	1575	1709	99
		225/55R18	1275	1392	1506	1618	1728	1874	102
		255/55R18	1545	1686	1825	1960	2094	2271	109
	50	225/50R18	1163	1269	1373	1475	1575	1709	99
		235/50R18	1238	1351	1462	1570	1677	1819	101
		245/50R18	1350	1474	1594	1713	1829	1984	104
	45	255/50R18	1425	1556	1683	1808	1931	2094	106
		215/45R18	975	1064	1151	1237	1321	1433	93
		225/45R18	1035	1130	1222	1313	1403	1521	95

Section 10
Load & Inflation

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
*Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					290 kPa*	LOAD INDEX	
			26	29	32	35	38			
18	45	235/45R18	1125	1228	1329	1427	1524	1653	98	
		245/45R18	1200	1310	1417	1523	1626	1764	100	
		255/45R18	1313	1433	1550	1665	1779	1929	103	
		275/45R18	1463	1596	1727	1856	1982	2150	107	
	40	205/40R18	795	868	939	1009	1077	1168	86	
		215/40R18	870	950	1027	1104	1179	1279	89	
		225/40R18	945	1032	1116	1199	1281	1389	92	
		235/40R18	1035	1130	1222	1313	1403	1521	95	
		245/40R18	1095	1195	1293	1389	1484	1609	97	
		255/40R18	1163	1269	1373	1475	1575	1709	99	
		265/40R18	1238	1351	1462	1570	1677	1819	101	
	35	215/35R18	750	819	886	952	1016	1102	84	
		225/35R18	818	892	965	1037	1108	1202	87	
		235/35R18	900	982	1063	1142	1220	1323	90	
		245/35R18	945	1032	1116	1199	1281	1389	92	
		255/35R18	1005	1097	1187	1275	1362	1477	94	
		265/35R18	1095	1195	1293	1389	1484	1609	97	
		275/35R18	1163	1269	1373	1475	1575	1709	99	
		285/35R18	1238	1351	1462	1570	1677	1819	101	
		295/35R18	1313	1433	1550	1665	1779	1929	103	
	30	285/30R18	1095	1195	1293	1389	1484	1609	97	
		295/30R18	1125	1228	1329	1427	1524	1653	98	
	19	65	235/65R19	1661	1783	1901	2015	2126	2271	109
		55	235/55R19	1388	1515	1639	1760	1880	2039	105
			255/55R19	1635	1785	1931	2074	2216	2403	111
		50	235/50R19	1313	1433	1550	1665	1779	1929	103
			245/50R19	1388	1515	1639	1760	1880	2039	105
			255/50R19	1463	1596	1727	1856	1982	2150	107
265/50R19			1590	1736	1878	2017	2155	2337	110	
275/50R19			1680	1834	1984	2132	2277	2469	112	
45		225/45R19	1065	1163	1258	1351	1443	1565	96	
		245/45R19	1275	1392	1506	1618	1728	1874	102	
		255/45R19	1350	1474	1594	1713	1829	1984	104	
		265/45R19	1492	1601	1707	1810	1909	2039	105	
		275/45R19	1500	1637	1772	1903	2033	2205	108	
		285/45R19	1635	1785	1931	2074	2216	2403	111	
40		225/40R19	975	1064	1151	1237	1321	1433	93	
		235/40R19	1065	1163	1258	1351	1443	1565	96	
		245/40R19	1125	1228	1329	1427	1524	1653	98	

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)					290 kPa*	LOAD INDEX	
			26	29	32	35	38			
19	40	255/40R19	1200	1310	1417	1523	1626	1764	100	
		265/40R19	1275	1392	1506	1618	1728	1874	102	
		275/40R19	1388	1515	1639	1760	1880	2039	105	
		285/40R19	1463	1596	1727	1856	1982	2150	107	
		295/40R19	1613	1732	1846	1958	2064	2205	108	
	35	215/35R19	773	843	912	980	1047	1135	85	
		225/35R19	840	917	992	1066	1138	1235	88	
		235/35R19	923	1007	1089	1170	1250	1356	91	
		245/35R19	975	1064	1151	1237	1321	1433	93	
		255/35R19	1065	1163	1258	1351	1443	1565	96	
		265/35R19	1125	1228	1329	1427	1524	1653	98	
		275/35R19	1200	1310	1417	1523	1626	1764	100	
		285/35R19	1313	1433	1550	1665	1779	1929	103	
	30	295/35R19	1350	1474	1594	1713	1829	1984	104	
		305/35R19	1425	1556	1683	1808	1931	2094	106	
		235/30R19	795	868	939	1009	1077	1168	86	
		245/30R19	870	950	1027	1104	1179	1279	89	
		255/30R19	923	1007	1089	1170	1250	1356	91	
		265/30R19	975	1064	1151	1237	1321	1433	93	
		275/30R19	1065	1163	1258	1351	1443	1565	96	
		285/30R19	1125	1228	1329	1427	1524	1653	98	
		295/30R19	1200	1310	1417	1523	1626	1764	100	
		305/30R19	1275	1392	1506	1618	1728	1874	102	
	20	55	325/30R19	1492	1601	1707	1810	1909	2039	105
			335/30R19	1572	1688	1800	1907	2012	2150	107
		50	345/30R19	1545	1686	1825	1960	2094	2271	109
			255/55R20	1709	1835	1956	2074	2188	2337	110
			275/55R20	1928	2104	2276	2446	2612	2833	117
255/50R20			1545	1686	1825	1960	2094	2271	109	
265/50R20			1635	1785	1931	2074	2216	2403	111	
275/50R20			1725	1883	2037	2189	2338	2535	113	
285/50R20			1876	2047	2214	2379	2541	2756	116	
305/50R20			2101	2292	2480	2664	2846	3086	120	
45	215/45R20	1035	1130	1222	1313	1403	1521	95		
	235/45R20	1200	1310	1417	1523	1626	1764	100		
	245/45R20	1313	1433	1550	1665	1779	1929	103		
	255/45R20	1388	1515	1639	1760	1880	2039	105		
	265/45R20	1500	1637	1772	1903	2033	2205	108		
	275/45R20	1590	1736	1878	2017	2155	2337	110		

Section 10
Load & Inflation

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
*Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)						LOAD INDEX
			26	29	32	35	38	290 kPa*	
			45	295/45R20	1770	1932	2090	2246	
40	235/40R20	1065	1163	1258	1351	1443	1565	96	
	245/40R20	1163	1269	1373	1475	1575	1709	99	
	255/40R20	1238	1351	1462	1570	1677	1819	101	
	265/40R20	1350	1474	1594	1713	1829	1984	104	
	275/40R20	1425	1556	1683	1808	1931	2094	106	
	305/40R20	1806	1939	2067	2191	2311	2469	112	
	35	225/35R20	900	982	1063	1142	1220	1323	90
235/35R20		945	1032	1116	1199	1281	1389	92	
245/35R20		1035	1130	1222	1313	1403	1521	95	
255/35R20		1095	1195	1293	1389	1484	1609	97	
265/35R20		1163	1269	1373	1475	1575	1709	99	
275/35R20		1275	1392	1506	1618	1728	1874	102	
285/35R20		1350	1474	1594	1713	1829	1984	104	
295/35R20		1492	1601	1707	1810	1909	2039	105	
305/35R20		1572	1688	1800	1907	2012	2150	107	
315/35R20		1590	1736	1878	2017	2155	2337	110	
30	225/30R20	773	843	912	980	1047	1135	85	
	235/30R20	840	917	992	1066	1138	1235	88	
	245/30R20	900	982	1063	1142	1220	1323	90	
	255/30R20	945	1032	1116	1199	1281	1389	92	
	265/30R20	1005	1097	1187	1275	1362	1477	94	
	275/30R20	1095	1195	1293	1389	1484	1609	97	
	285/30R20	1163	1269	1373	1475	1575	1709	99	
	295/30R20	1238	1351	1462	1570	1677	1819	101	
	305/30R20	1313	1433	1550	1665	1779	1929	103	
	335/30R20	1500	1637	1772	1903	2033	2205	108	
25	285/25R20	975	1064	1151	1237	1321	1433	93	
	295/25R20	1035	1130	1222	1313	1403	1521	95	
	305/25R20	1095	1195	1293	1389	1484	1609	97	
	315/25R20	1163	1269	1373	1475	1575	1709	99	
	325/25R20	1238	1351	1462	1570	1677	1819	101	
	335/25R20	1313	1433	1550	1665	1779	1929	103	
21	50	275/50R21	1855	1991	2123	2250	2373	2535	113
	45	275/45R21	1709	1835	1956	2074	2188	2337	110
		285/45R21	1725	1883	2037	2189	2338	2535	113
	40	265/40R21	1388	1515	1639	1760	1880	2039	105
		285/40R21	1661	1783	1901	2015	2126	2271	109
		295/40R21	1758	1887	2012	2132	2250	2403	111

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.

*Conversion 100 kPa = 14.5 psi

European Metric Reinforced Load and Inflation Tables

Tire load limits at various cold inflation pressures

R I M D I A	S E R I E S	TIRE SIZE DESIGNATION	Maximum Load (lbs) at Pressure (psi)						LOAD INDEX
			26	29	32	35	38	290 kPa*	
21	35	245/35R21	1065	1163	1258	1351	1443	1565	96
		265/35R21	1238	1351	1462	1570	1677	1819	101
		275/35R21	1313	1433	1550	1665	1779	1929	103
		285/35R21	1388	1515	1639	1760	1880	2039	105
		295/35R21	1463	1596	1727	1856	1982	2150	107
	30	245/30R21	923	1007	1089	1170	1250	1356	91
		255/30R21	975	1064	1151	1237	1321	1433	93
		265/30R21	1065	1163	1258	1351	1443	1565	96
		275/30R21	1125	1228	1329	1427	1524	1653	98
		285/30R21	1200	1310	1417	1523	1626	1764	100
		295/30R21	1275	1392	1506	1618	1728	1874	102
		305/30R21	1350	1474	1594	1713	1829	1984	104
	25	315/30R21	1492	1601	1707	1810	1909	2039	105
		295/25R21	1065	1163	1258	1351	1443	1565	96
		305/25R21	1125	1228	1329	1427	1524	1653	98
		325/25R21	1275	1392	1506	1618	1728	1874	102
22	45	355/25R21	1572	1688	1800	1907	2012	2150	107
		285/45R22	1770	1932	2090	2246	2398	2601	114
	40	295/45R22	1876	2047	2214	2379	2541	2756	116
		275/40R22	1572	1688	1800	1907	2012	2150	107
		295/40R22	1680	1834	1984	2132	2277	2469	112
	35	305/40R22	1770	1932	2090	2246	2398	2601	114
		285/35R22	1425	1556	1683	1808	1931	2094	106
	30	305/35R22	1590	1736	1878	2017	2155	2337	110
		235/30R22	900	982	1063	1142	1220	1323	90
		255/30R22	1035	1130	1222	1313	1403	1521	95
		265/30R22	1095	1195	1293	1389	1484	1609	97
		295/30R22	1313	1433	1550	1665	1779	1929	103
		305/30R22	1388	1515	1639	1760	1880	2039	105
		25	275/25R22	975	1064	1151	1237	1321	1433
	295/25R22		1095	1195	1293	1389	1484	1609	97
305/25R22	1163		1269	1373	1475	1575	1709	99	
23	40	305/40R23	1823	1989	2152	2312	2470	2679	115
	25	315/25R23	1275	1392	1506	1618	1728	1874	102
24	35	305/35R24	1680	1834	1984	2132	2277	2469	112

Note: Data above is based on the European Tire and Rim Technical Organization (ETRTO) standards and lbs. listed are approximate conversions.
*Conversion 100 kPa = 14.5 psi

Light Truck Load and Inflation Tables

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	S E R I E S	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
			25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
14	75	LT175/75R14			955	1050	1140	1235(C)									
		LT185/75R14			1040	1140	1240	1355(C)									
		LT195/75R14			1115	1225	1330	1435(C)	1530	1625	1710(D)						
		LT215/75R14			1285	1415	1535	1655(C)	1765	1880	1985(D)						
	70	LT205/70R14			1150	1265	1370	1475(C)	1580	1675	1765(D)	1870	1960	2040(E)			
		LT215/70R14			1235	1355	1470	1610(C)									
15	80	LT215/80R15			1400	1535	1665	1820	1920	2040	2150(D)						
	75	LT195/75R15			1165	1280	1390	1520(C)									
		LT205/75R15			1260	1385	1500	1655(C)	1730	1840	1930(D)						
		LT215/75R15			1345	1475	1605	1765(C)	1845	1960	2095(D)						
		LT225/75R15			1445	1585	1720	1875(C)	1980	2105	2205(D)						
		LT235/75R15			1530	1680	1825	1985(C)	2100	2235	2335(D)	2490	2610	2755(E)			
		LT245/75R15			1635	1795	1950	2150(C)									
		LT255/75R15			1730	1900	2065	2270(C)									
	70	LT265/75R15			1840	2020	2195	2405(C)									
		LT235/70R15			1465	1610	1750	1875(C)	2010	2140	2270(D)	2380	2500	2600(E)			
		LT245/70R15			1560	1710	1860	2040(C)									
		LT255/70R15			1655	1815	1970	2150(C)	2270	2410	2535(D)						
		LT265/70R15			1750	1925	2090	2270(C)									
		LT285/70R15			1955	2145	2330	2535(C)	2680	2850	3000(D)						
	65	LT315/70R15			2335(C)	2500	2715	2910(D)									
65		LT245/65R15			1450	1595	1730	1875(C)									
60		LT325/60R15			2095(C)												
16	85	LT215/85R16			1495	1640	1785	1940(C)	2050	2180	2335(D)	2430	2550	2680(E)			3000(F)
		LT235/85R16			1700	1870	2030	2205(C)	2335	2485	2623(D)	2765	2905	3042(E)			3415(F)
		LT255/85R16			1920	2110	2290	2470(C)	2635	2805	3000(D)	3120	3275	3415(E)			
	80	LT325/80R16			2755	2970	3225	3525(D)									

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Tables

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	S E R I E S	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)															
			25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	
16	75	LT225/75R16			1500	1650	1790	1940(C)	2060	2190	2335(D)	2440	2560	2680(E)			3000(F)	
		LT245/75R16			1700	1870	2030	2205(C)	2335	2480	2623(D)	2765	2900	3042(E)			3415(F)	
		LT265/75R16			1910	2100	2280	2470(C)	2625	2790	3000(D)	3105	3260	3415(E)				
		LT285/75R16			2130	2340	2540	2755(C)	2925	3110	3305(D)	3465	3635	3750(E)				
		LT295/75R16			2240	2460	2670	2910(C)	3070	3265	3415(D)	3635	3815	3970(E)				
		LT315/75R16			2535(C)	2715	2950	3195(D)	3395	3610	3860(E)							
		LT345/75R16			2910	3135	3405	3750(D)										
	LT365/75R16			3195(C)														
	70	LT215/70R16			1340	1475	1600	1765(C)										
		LT225/70R16			1435	1575	1710	1875(C)										
		LT235/70R16			1525	1675	1820	1985(C)	2095	2225	2335(D)							
		LT245/70R16			1620	1780	1935	2095(C)	2225	2365	2535(D)	2635	2765	2910(E)				
		LT255/70R16			1720	1890	2050	2205(C)	2360	2510	2680(D)							
		LT265/70R16			1820	2000	2170	2335(C)	2500	2655	2835(D)	2955	3105	3195(E)				
		LT275/70R16			1925	2110	2295	2470(C)	2640	2805	3000(D)							
		LT305/70R16			2270	2465	2680	2910(D)	3085	3275	3525(E)	3650	3830	3970(F)				
		LT315/70R16			2405	2590	2815	3085(D)										
		LT355/70R16			2910	3115	3380	3640(D)										
	LT365/70R16			3000	3250	3530	3860(D)											
	LT395/70R16			3415(C)														
	65	LT215/65R16			1260	1380	1500	1655	1725	1835	1930(D)							
		LT375/65R16			2910	3165	3435	3750(D)										
	60	LT285/60R16			1750	1920	2085	2270(C)										
		LT315/55R16			1875	2020	2195	2405(D)										
	55	LT345/55R16			2150	2325	2525	2755(D)										
		LT375/55R16			2470	2630	2855	3085	3285	3490	3750(E)							
	17	80	LT235/80R17			1725	1895	2055	2270	2370	2515	2680	2805	2940	3085(E)			

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Tables

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	S E R I E S	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
			25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
17	80	LT255/80R17			1945	2135	2320	2535	2670	2835	3000	3065	3130	3195(E)			
	75	LT225/75R17			1565	1720	1865	2040	2145	2280	2405	2540	2670	2755(E)			
		LT245/75R17			1770	1945	2110	2270	2430	2580	2755	2875	3020	3195(E)			
		LT255/75R17			1870	2055	2230	2405(C)									
		LT285/75R17			2215	2430	2640	2835	2955	3075	3195(D)	3195	3195	3195(E)			
		LT225/70R17			1495	1640	1780	1930	2050	2175	2335(D)						
	70	LT245/70R17			1690	1855	2010	2205(C)	2315	2460	2600(D)	2740	2875	3000(E)			
		LT255/70R17			1790	1965	2130	2335	2455	2610	2755	2905	3050	3195(E)			
		LT265/70R17			1890	2075	2255	2470(C)	2595	2760	2910(D)	3005	3100	3195(E)			
		LT275/70R17			2000	2195	2380	2600(C)	2760	2925	3085	3120	3160	3195(E)			
		LT285/70R17			2105	2315	2510	2755(C)	2900	3050	3195(D)	3195	3195	3195(E)			
		LT305/70R17			2405	2560	2780	3000(D)	3065	3130	3195(E)						
		LT315/70R17			2535(C)	2685	2915	3195(D)	3195	3195	3195(E)						
		LT355/70R17			3000	3065	3130	3195(D)									
	65	LT245/65R17			1575	1730	1875	2040(C)	2160	2295	2405(D)						
		LT255/65R17			1675	1840	1995	2150	2300	2445	2600(D)						
		LT265/65R17			1765	1935	2105	2270	2420	2570	2755(D)	2865	3005	3085(E)			
		LT275/65R17			1870	2055	2230	2405	2565	2725	2910(D)	3005	3100	3195(E)			
		LT305/65R17			2205	2385	2590	2835	2955	3075	3195(E)						
	60	LT235/60R17			1375	1510	1640	1765	1890	2005	2150	2235	2345	2470(E)			
LT285/60R17				1820	1995	2170	2335(C)										
55	LT345/55R17			2270	2410	2620	2835(D)										
18	70	LT255/70R18			1855	2035	2210	2405	2545	2705	2835(D)						
		LT265/70R18			1960	2155	2340	2535	2690	2860	3085	3185	3345	3525(E)			
		LT275/70R18			2070	2270	2470	2680(C)	2840	3020	3195	3360	3530	3640(E)			
		LT285/70R18			2180	2395	2600	2835	2995	3180	3415	3545	3720	3860(E)			
	65	LT235/65R18			1565	1700	1845	1985	2120	2255	2405	2515	2635	2755(E)			

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Tables

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	S E R I E S	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
			25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
18	65	LT255/65R18			1740	1910	2070	2270	2385	2535	2680	2825	2965	3085(E)			
		LT265/65R18			1830	2010	2180	2405	2510	2670	2835(D)	2970	3120	3305(E)			
		LT275/65R18			1940	2130	2310	2535(C)	2660	2825	3000	3150	3305	3415(E)			
		LT285/65R18			2035	2235	2425	2600	2790	2965	3195(D)	3305	3470	3640(E)			
		LT305/65R18			2335	2470	2680	2910	3085	3280	3525(E)						
		LT325/65R18			2535	2715	2945	3195(D)	3390	3605	3860(E)						
		LT355/65R18			2910	3110	3375	3640	3750	3860	3970(E)						
	LT395/65R18			3415(C)													
	60	LT265/60R18			1695	1865	2025	2205	2330	2475	2600	2755	2895	3000(E)			
		LT285/60R18			1885	2070	2250	2470	2585	2750	2910(D)	3060	3215	3305(E)			
		LT305/60R18			2150	2285	2480	2680	2855	3035	3195(E)						
		LT325/60R18			2335	2510	2725	3000	3135	3335	3525(E)						
		LT375/60R18			2910	3110	3375	3640(D)									
	55	LT255/55R18			1460	1605	1745	1875	2005	2135	2270(D)						
50	LT375/50R18			2335	2530	2745	3000	3160	3355	3525(E)							
20	75	LT325/75R20			3085	3260	3540	3860(D)									
	65	LT275/65R20			2080	2280	2475	2680	2850	3030	3195	3375	3540	3750(E)			
		LT285/65R20			2180	2390	2600	2835	2990	3175	3415	3540	3715	3860(E)			
	60	LT265/60R20			1825	2000	2175	2335	2500	2660	2835	2960	3110	3195(E)			
		LT275/60R20			1920	2110	2290	2470	2635	2800	3000	3120	3275	3415(E)			
		LT305/60R20			2270	2445	2655	2910(D)	3055	3250	3415(E)						
	LT325/60R20			2535	2680	2915	3195(D)	3350	3560	3750(E)							
	55	LT275/55R20			1750	1920	2085	2270	2400	2550	2680(D)	2845	2985	3085(E)			
		LT285/55R20			1850	2030	2205	2405	2535	2695	2835(D)	3005	3150	3305(E)			
		LT305/55R20			2095	2235	2425	2680	2795	2970	3195(E)						
50	LT325/50R20			2040	2200	2390	2600	2750	2920	3085(E)							

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Tables

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	S E R I E S	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
			25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
22	50	LT325/50R22			2205	2350	2550	2755	2935	3120	3305(E)						
	55	LT325/55R22			2470	2610	2835	3085(D)									
		LT335/55R22			2535	2715	2950	3195(D)									
	60	LT325/60R22			2680	2855	3100	3415(D)	3570	3795	3970(E)						
24	45	LT325/45R24			2040	2190	2380	2600	2735	2910	3085(E)						

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Table

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
		25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
14	27x8.50R14LT	940	1075	1200(B)	1305	1415	1520(C)									
15	6.70R15LT			1210	1320	1430	1520(C)	1630	1720	1820(D)	1900	1980	2040(E)			
	7.00R15LT			1350	1480	1610	1710(C)	1830	1940	2040(D)	2130	2220	2335(E)			
	29x9.50R15LT	1135	1290	1435(B)	1575	1700	1820(C)									
	30x9.50R15LT	1240	1410	1565(B)	1715	1855	1985(C)									
	33x9.50R15LT	1565	1780	1980	2170	2345	2535(C)									
	31x10.50R15LT	1400	1595	1765(B)	1945	2100	2270(C)									
	33x10.50R15LT	1630	1855	2040(B)	2260	2445	2600(C)									
	31x11.50R15LT	1455	1660	1820(B)	2020	2185	2335(C)									
	32x11.50R15LT	1575	1795	1985(B)	2185	2360	2535(C)									
	31x12.50R15LT	1520	1715	1930(C)												
33x12.50R15LT	1765(B)	2000	2205(C)													
35x12.50R15LT	2040	2295	2535(C)													
37x12.50R15LT	2270(B)	2600	2910(C)													
35x13.50R15LT	2095	2370	2600(C)													
37x13.50R15LT	2335	2690	3000(C)													
36x14.50R15LT	2270(B)	2610	2910(C)													
33x15.50R15LT	1930	2185	2405(C)													
36x15.50R15LT	2335	2690	3000(C)													
38x15.50R15LT	2680	3040	3415(C)													
16	6.50R16LT			1270	1390	1500	1610(C)	1710	1800	1930(D)	1990	2080	2150(E)			
	7.50R16LT			1620	1770	1930	2040(C)	2190	2310	2470(D)	2560	2670	2755(E)			
16.5	8.00*16.5LT			1360	1490	1610	1765(C)	1840	1945	2040(D)	2145	2240	2335(E)			
	8.75*16.5LT			1570	1720	1850	1985(C)	2110	2240	2405(D)	2470	2570	2680(E)			
	9.50*16.5LT			1860	2030	2190	2405(C)	2500	2650	2835(D)	2920	3050	3195(E)			
	10*16.5LT			1875(B)	2010	2170	2335(C)	2480	2620	2755(D)	2885	3010	3195(E)			
	12*16.5LT			2405(C)	2590	2800	3000(D)	3190	3370	3640(E)	3720	3885	4080(F)			
	31x10.50R16.5LT			1830(B)	2000	2165	2320(C)	2465	2605	2745(D)						

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
 •Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
 •Check sidewall for maximum allowable load if the tire is to be used in dual applications.

Light Truck Load and Inflation Table

For Light Truck Metric Radial Tires For Single Usage

R I M D I A	Tire Size Designation	Maximum Load (lbs) at Pressure (psi)														
		25	30	35	40	45	50	55	60	65	70	75	80	85	90	95
16.5	33x12.50R16.5LT			2310(C)	2530	2735	2930(D)									
17	33x12.50R17LT	1610	1850	2040(C)	2255	2440	2600(D)	2780	2935	3085(E)						
	35x12.50R17LT	1875	2155	2405(C)	2625	2840	3000(D)	3065	3130	3195(E)						
	37x12.50R17LT	2150	2470	2755(C)	3005	3250	3525(D)									
	37x13.50R17LT	2205	2550	2835	2955	3075	3195(D)									
	38x13.50R17LT	2405	2715	3000(C)												
	39x13.50R17LT	2535	2885	3195(C)												
	40x13.50R17LT	2680	2940	3195(C)												
	36x14.50R17LT	2150	2455	2755	2900	3050	3195(D)									
	38x14.50R17LT	2470	2800	3085	3120	3160	3195(D)									
	38x15.50R17LT	2535	2885	3195(C)												
40x14.50R17LT	2755	2975	3195(C)													
18	34x12.50R18LT	1710	1920	2150	2340	2530	2680	2880	3045	3195(E)						
	35x12.50R18LT	1820	2075	2335	2530	2735	2910(D)	3115	3295	3415(E)						
	37x12.50R18LT	2095	2395	2680(C)	2915	3150	3415(D)	3590	3795	3970(E)						
	35x13.50R18LT	1875	2140	2405	2605	2815	3000(D)									
	36x13.50R18LT	2040	2305	2535	2805	3030	3195(D)									
	37x13.50R18LT	2150	2470	2755	3005	3250	3525(D)	3675	3820	3970(E)						
	36x14.50R18LT	2095	2370	2600	2885	3115	3305(D)									
	38x14.50R18LT	2405	2715	3000	3305	3575	3860(D)									
	40x14.50R18LT	2680	3075	3415(C)												
	38x15.50R18LT	2470	2800	3085	3405	3685	3970(D)									
20	33x12.50R20LT	1390	1580	1765	1920	2075	2205	2500	2500	2600(E)						
	37x12.50R20LT	1930	2225	2470	2705	2925	3085(D)	3335	3525	3750(E)						
	40x13.50R20LT	2470	2815	3085	3425	3705	3970(D)	3970	3970	3970(E)						
	38x14.50R20LT	2205	2535	2835	3080	3330	3525(D)									
	40x14.50R20LT	2535	2895	3195(C)												
	42x14.50R20LT	2835	3275	3640(C)												

NOTES: •All Tire Sizes represent Light Truck RADIAL Metric Tires for Single use.
•Letters in the Parentheses denote Load Range for which Bold Face Loads are maximum.

•Always use approved tire and rim combinations for diameter and contours.
•Check sidewall for maximum allowable load if the tire is to be used in dual applications.