

REFERENCES AND TECHNICAL CHARACTERISTICS

CAI	DESIGNATION	TYPE	PROFILE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE SECTION (MM)	INFLATED DIAMETER (MM)	ROLLING CIRCUMFERENCE (MM)
370109	18/58 - 15	S9L	Hard	8	178	220	583	1832
698915	18/58 - 15	P2L	Rain	8	179	220	588	1847
N 862104	19/57 - 15	S8M	Medium	7,0	185	206	573	1774
N 964131	19/57 - 15	P2H	Rain	7,0	185	206	573	1762
273199	23/61 - 16	S9L	Hard	10	236	276	616	1935
853299	23/61 - 16	P2L	Rain	10	240	276	620	1947
853709	20/61 - 17	S8L	Medium	8	190	225	604	1890
587121	20/61 - 17	S8M RFID	Medium	8	187	219	606	1870
721630	20/61 - 17	S9M RFID	Hard	8	187	219	606	1870
829591	20/61 - 17	P2G	Rain	8	191	223	604	1854
N 178573	20/61 - 17	P2H	Rain	8	191	223	604	1854
146154	24/61 - 17	S8L	Medium	9	235	248	605	1857
N 130580	24/61 - 17	S8M RFID	Medium	9	235	250	605	1857
046924	24/61 - 17	P2G	Rain	9	235	250	605	1857
N 201854	24/61 - 17	P2H	Rain	9	224	248	610	1861
987692	24/64 - 17	S8M RFID	Medium	9	226	254	639	2007
361832	24/64 - 17	P2G	Rain	9	226	254	639	2007
N 246828	24/64 - 18	S9M	Medium	9,5	225	255	646	2000
N 503749	24/64 - 18	P2L	Rain	9,5	225	255	651	2000
373234	25/64 - 18	S8L	Medium	10	249	271	642	1990
N 208081	25/64 - 18	S8M RFID	Medium			PENDING		
205461	25/64 - 18	S9L	Hard	10	249	271	642	1990
N 173686	25/64 - 18	S9M RFID	Hard			PENDING		
448993	25/64 - 18	P2L	Rain	10	231	269	647	2031

 The technical data contained in this document is given for information purposes only. Checks must be made under real conditions.

N = NEW

CAI	DESIGNATION	TYPE	PROFILE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE SECTION (MM)	INFLATED DIAMETER (MM)	ROLLING CIRCUMFERENCE (MM)
873904	27/65 - 18	S8L	Medium	11	260	298	648	1990
320739	27/65 - 18	S8M RFID	Medium	11	260	284	650	2015
033685	27/65 - 18	S9L	Hard	11	260	298	648	1990
146207	27/65 - 18	S9M RFID	Hard	11	260	284	650	2015
463077	27/65 - 18	P2L	Rain	11	260	299	652	2048
765707	27/68 - 18	P2L	Rain	11	255	295	684	2147
344563	30/65 - 18	S7M RFID	Soft	12,5	288	329	650	1996
050951	30/65 - 18	S8M RFID	Medium	12,5	288	329	650	1996
520590	30/65 - 18	S9M RFID	Hard	12,5	288	329	650	1996
619653	30/65 - 18	P2L	Rain	12,5	295	325	653	2057
654850	30/68 - 18	S7M RFID	Medium	12	306	327	678	2104
377912	30/68 - 18	S8M RFID	Hard	12	306	327	678	2104
763553	30/68 - 18	S9M RFID	Hard	12	306	327	678	2104
447350	30/68 - 18	P2L	Rain	12,5	311	329	684	2150
272434	33/68 - 18	S8M RFID	Medium	13	312	352	682	2146
N 120877	33/68 - 18	S9M RFID	Hard	13	312	352	682	2146
N 620053	31/71 - 18	S7M RFID	Soft	13	310	347	712	2185
593443	31/71 - 18	S8M RFID	Medium	13	310	347	712	2185
927289	31/71 - 18	S9M RFID	Hard	13	310	347	712	2185
797297	31/71 - 18	P2L	Rain	13	313	347	711	2232
948272	24/65 - 19	S8M RFID	Medium			PENDING		
N 088188	24/65 - 19	S9M RFID	Medium			PENDING		
N 206124	24/65 - 19	P2L	Rain			PENDING		
N 588214	24/65 - 19	P2H	Rain			PENDING		
454416	28/69 - 19	P2H	Rain			PENDING		
350154	31/71 - 19	S9M RFID	Hard	13	316	343	709	2192
398275	31/71 - 19	P2L	Rain	13	316	344	711	2232

⚠ The technical data contained in this document is given for information purposes only.
Checks must be made under real conditions.

N = NEW