



TAURUS POINT 7S

- ✓ Specific tread pattern
- ✓ Outstanding traction
- ✓ Effective self-cleaning grooves
- ✓ Tubeless

SIZES

400/75 R38 138A8/135B TL

TAURUS POINT 7S

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)		Tread depth (mm)
38	400/75 R38 138A8/135B TL (1,5 R38)	924529	404	1565	708	4711	DW14L		DW12 W12 W14L		796	235		42
Bar	0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4	0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4	1.5 1.6 1.7 1.8 1.9 2.0	2.2 2.3 2.5 2.6 2.8 2.9	3.1 3.2 3.4 3.5 3.7 3.8	4.1 4.2 4.4 4.5 4.7 4.8	5.1 5.2 5.4 5.5 5.7 5.8	6.1 6.2 6.4 6.5 6.7 6.8	7.1 7.2 7.4 7.5 7.7 7.8	8.1 8.2 8.4 8.5 8.7 8.8	9.1 9.2 9.4 9.5 9.7 9.8	10.1 10.2 10.4 10.5 10.7 10.8	11.1 11.2 11.4 11.5 11.7 11.8	12.1 12.2 12.4 12.5 12.7 12.8
Psi	9 10 12 13 15 16 17 19 20	9 10 12 13 15 16 17 19 20	22 23 25 26 28 29	31 32 34 35 37 38	41 42 44 45 47 48	51 52 54 55 57 58	61 62 64 65 67 68	71 72 74 75 77 78	81 82 84 85 87 88	91 92 94 95 97 98	101 102 104 105 107 108	111 112 114 115 117 118	121 122 124 125 127 128	131 132 134 135 137 138
10 km/h **	1590 1730 1870 2010	2145 2285 2425 2565	2705 2845 2985 3120	3260 3400 3540										
30 km/h	1370 1485 1600 1720	1835 1950 2065 2180	2300 2415 2530											
40 km/h		1690 1800 1915 2025	2135 2250 2360											
50 km/h			1750 1845 1935 2030	2120										

*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
 - When using single TYRE configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50%
- **10 km/h LT (Low Torque) (max speed 10 km/h).