

RIKEN

TRUCKS AND BUSES TYRES MADE IN EUROPE



AFFORDABLE AND SAFE

- o Extra wide shoulders
- o Reinforced steel belts
- o Regroovable and retreadable

PEACE OF MIND

- o Easy to fit
- o Reliable
- o Efficient torque transmission

100% EUROPEAN


- o Designed for the European conditions (M+S / 3PMSF)
- o Complying with regulations (EU labelling, REACH)
- o Made in Europe (ISO 9001 & 14001 certifications)

Section: 285 to 315 mm

Diameter: 17.5" to 22.5"

Series: 60 to 90

Speed Index: J-M



(1) Fuel efficiency (from A to E) - (2) Wet grip (from A to E)
(3) External rolling noise class (from A to C) - (4) External rolling noise measured value (decibel)
*Image for 385/65 R 22.5 RIKEN ROAD READY T

www.riken.com
Just efficient

RIKEN

MEDIUM TRUCK & LOW-BED TRAILER REGIONAL & LONG HAUL USE



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
205/75R17.5 Steer	124/122M		D	C	A - 68 dB	M+S		TRACTION	1
215/75R17.5 Steer	126/124M		D	C	A - 68 dB	M+S		TRACTION	1
235/75R17.5 Steer	132/130M		D	C	A - 68 dB	M+S		TRACTION	1
245/70R17.5 Steer	136/134M		D	B	A - 68 dB	M+S		TRACTION	1
265/70R19.5 Steer	140/138M		C	C	A - 68 dB	M+S		TRACTION	1
285/70R19.5 Steer	146/144L		C	B	A - 72 dB	M+S		TRACTION	1



TRAILER



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
215/75R17.5 Trailer	135/133J		D	B	A - 69 dB	M+S		FRT ⁽⁵⁾	2
235/75R17.5 Trailer	143/141J	144F	C	B	A - 69 dB	M+S		FRT ⁽⁵⁾	2
245/70R17.5 Trailer	143/141J	144F	C	B	A - 69 dB	M+S		FRT ⁽⁵⁾	2
265/70R19.5 Trailer	143/141J		C	B	A - 69 dB	M+S		FRT ⁽⁵⁾	2

● Recommended position ● Possible position

REGROOVING

Reference	1	2
Blade	R3	R3
Width	6 to 8 mm	6 to 8 mm
Max Depth	2 mm	2 mm

All tyres are compliant with UNECE/R54 and ETRTO standards

- (1) Fuel efficiency (from A to E)
- (2) Wet grip (from A to E)
- (3) External rolling noise class (from A to C) & External rolling noise measured value (decibel)
- (4) Respect the positions, fitting direction, direction of rotation and any relevant instructions when mentioned on the tyre sidewalls
- (5) Free Rolling Tyre.

HEAVY TRUCK
REGIONAL & LONG HAUL USE



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
295/80R22.5 Steer	152/148M		C	C	A - 70 dB	M+S			3
315/80R22.5 Steer	156/150L		C	B	A - 70 dB	M+S			3
315/70R22.5 Steer	154/150L		C	C	B - 72 dB	M+S			3
385/65R22.5 Steer	160K	158L	C	B	B - 72 dB	M+S			3

*Available for tyres produced starting with September 2021.



DRIVE




FITTING DIRECTION⁽⁴⁾

Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
295/80R22.5 Drive	152/148M		C	C	A - 73 dB	M+S		TRACTION	4
315/80R22.5 Drive	156/150L		C	C	A - 73 dB	M+S		TRACTION	4
315/70R22.5 Drive	154/150L		C	C	A - 73 dB	M+S		TRACTION	4



TRAILER



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
385/65R22.5 Trailer	160K		C	C	A - 70 dB	M+S		FRT ⁽⁵⁾	5

*Available for tyres produced starting with September 2021.


● Recommended position ● Possible position

REGROOVING

Reference	3	4	5
Blade	R3	R3	R4
Width	7 to 8 mm	7 to 8 mm	7 to 8 mm
Max Depth	2 mm	2 mm	2 mm



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
275/70R22.5 Steer	150/148J		D	B	A - 71 dB	M+S		TRACTION	6



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
315/80R22.5 Steer*	156/150K		C	B	B - 71 dB	M+S			7
13R22.5 Steer	156/150K		D	B	A - 69 dB	M+S			7
385/65R22.5 Steer**	160K	158L	C	C	B - 72 dB	M+S			7

*Available for tyres produced starting with September 2021.



DRIVE



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
315/80R22.5 Drive	156/150K		D	B	B - 76 dB	M+S		TRACTION	8
13R22.5 Drive	156/150K		D	B	B - 76 dB	M+S		TRACTION	8

● Recommended position ● Possible position

REGROOVING

Reference	6	7	8
Blade	R3	R4	R3
Width	10 mm	10 mm	10 mm
Max Depth	2 mm	2 mm	2 mm

All tyres are compliant with UNECE/R54 and ETRTO standards - (1) Fuel efficiency (from A to E) - (2) Wet grip (from A to E)
(3) External rolling noise class (from A to C) & External rolling noise measured value (decibel).